




-1, -2; AS SHOWN	LOC	DIST	REVISIONS 変更					
	J		P	LTR	DESCRIPTION	DATE	DWN	APVD
				D1	REVISED PER ECO-11-005030	11MAR11	RK	HMR




1 運用スリーブ型番
: 1717268-X, 176497-X, 2013799-X

1 APPLICABLE SLEEVE P/N
: 1717268-X, 176497-X, 2013799-X



LOOSE PIECE NO. ばら状端子型番	PRE TIN COPPER ALLOY 0.4t 錫めっき付銅合金 0.4t	175057-2
	PRE TIN BRASS 0.4t 錫めっき付 黄銅 0.4t	175057-1
	MATERIAL 材 料	P/N 型 番

WIRE RANGE 包合電線断面積	AWG #18-#12 0.75~3.37 mm ²	INSULATION DIA 被覆外径	2.8~4.1 mmφ
-----------------------	--	------------------------	-------------

DIMENSIONS: 単位: 耗 mm	DWN J.SATO	15NOV2007	MATERIAL 材料 表参照 SEE TABLE		FINISH 仕上
	CHK S.MANABE	15NOV2007	TE Connectivity		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差	APVD S.MANABE	15NOV2007			
0 PLC ±	PRODUCT SPEC 製品規格		NAME 名称 250 SERIES FLAG POSITIVE LOCK EX 250 シリーズ 旗型ポジティブロックEX		
1 PLC ± 10 ≥: ±0.2	108-5254				
2 PLC ± 30 ≥: ±0.25	APPLICATION SPEC 取付適用規格		SIZE CAGE CODE DRAWING NO 番号		
3 PLC ± 100 ≥: ±0.3	114-5122				
4 PLC ±	WEIGHT		RESTRICTED TO		
ANGLES ± 3°					
			A4 00779 C-175057		
CUSTOMER DRAWING			SCALE 尺度 NTS	SHEET 1 OF 1	REV D1

