

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

MAY, 2008

© COPYRIGHT 2008

BY Tyco Electronics Japan G.K.

ALL RIGHTS RESERVED.

LOC
JDIST
-

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-----------------------|-----------|-----|------|
| | B | REVISED ECR-12-006355 | 11APR2012 | H.O | N.Y |
| | C | REVISED ECR-14-019215 | 29JAN2015 | K.R | N.Y |

- 1 : AS SHOWN

有効ネジ深さ10mm
VALID FOR 10mm 3

NOTE

1 MATERIAL:
CASE: POLYBUTYLEN TEREPHTHALATE (94V-0)
COLOR: BLACK
RUBBER: NITRILE-BUTADIENE RUBBER
COLOR: BLACK

2. THE SHAPE, SIZE AND POSITION OF THE CHARACTER SHOW THE OUTLINE. THEY DON'T SHOW DETAILS.

3 APPLY TO COMMERCIAL-RELEASE CABLE GLAND (M20XP1.5) FOR WATERPROOFING AND HOLDING OF CAPTURE CABLE

注記

1 材料:
ケース: ポリブチレンテレフタレート (94V-0)
色: 黒
ゴム: ニトリルブタジエンゴム
色: 黒

2. 文字の形状、大きさ、および位置については、大略を示すものであり、詳細を示すものではありません。

3 キャプタイヤケーブルの防水と保持には、市販のケーブルグランド (M20XP1.5) を使用ください

ATTENTION

本図面は技術検討用図面のため、記載の形状・寸法は変更する可能性があります。
最新の形状・寸法については、弊社営業部にお問い合わせください。

| | | | | | | | | | | | | | | | | |
|---|---------|-------------------------------|--|-------------------------|------|-------|-------|-------|--------|-------|---------|--------|----|---------------------------|------------|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN T. SAMI 22OCT2007 | TE Connectivity | | | | | | | | | | | | | |
| DIMENSIONS: mm | | CHK A. OISHI 13MAY2008 | | | | | | | | | | | | | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.3 | | APVD A. OISHI 13MAY2008 | NAME MULTIPLE ENCLOSURE CONN. MOLD TYPE PLUG CASE | | | | | | | | | | | | | |
| <table border="1"> <tr> <td>Ø PLC</td> <td>±</td> </tr> <tr> <td>1 PLC</td> <td>±0.5</td> </tr> <tr> <td>2 PLC</td> <td>±0.13</td> </tr> <tr> <td>3 PLC</td> <td>±0.013</td> </tr> <tr> <td>4 PLC</td> <td>±0.000J</td> </tr> <tr> <td>ANGLES</td> <td>±3</td> </tr> </table> | | Ø PLC | ± | 1 PLC | ±0.5 | 2 PLC | ±0.13 | 3 PLC | ±0.013 | 4 PLC | ±0.000J | ANGLES | ±3 | PRODUCT SPEC 108-78566 | SIZE A3 | |
| Ø PLC | ± | | | | | | | | | | | | | | | |
| 1 PLC | ±0.5 | | | | | | | | | | | | | | | |
| 2 PLC | ±0.13 | | | | | | | | | | | | | | | |
| 3 PLC | ±0.013 | | | | | | | | | | | | | | | |
| 4 PLC | ±0.000J | | | | | | | | | | | | | | | |
| ANGLES | ±3 | | | | | | | | | | | | | | | |
| MATERIAL | | APPLICATION SPEC 411-78293 | CAGE CODE 00779 | DRAWING NO C-1981919 | | | | | | | | | | | | |
| FINISH - | | WEIGHT 23.9 g | RESTRICTED TO - | | | | | | | | | | | | | |
| | | CUSTOMER DRAWING | | SCALE | | | | | | | | | | | | |
| | | SHEET | | OF | | | | | | | | | | | | |
| | | REV C | | | | | | | | | | | | | | |

1470-19 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1981919-1](#)