


NOTES:

- 1) ELECTRICAL SPECIFICATIONS:
  - 1-1. VOLTAGE RATING: 125V/AC
  - 1-2. CURRENT RATING: 1.5A
  - 1-3. INSULATION RESISTANCE: 500MEG.OHM MIN
  - 1-4. CONTACT RESISTANCE: 30 MILL.OHM MAX
  - 1-5. WITHSTANDING VOLTAGE: 1000V AC
  - 1-6. OPERATION TEMPERATURE: -40° TO +85°
  - 1-7. DURABILITY: 3000 CYCLES



RJ45 Pin Assignment:

Pin No.	Name
1	Tranceive Data+
2	Tranceive Data-
3	Receive Data+
4	Not connected
5	Not connected
6	Receive Data-
7	Not connected
8	Not connected

ITEM	NAME	Q'TY	MATERIAL	FINISH	REMARK
3	SHELL	1	COPPER ALLOY	Ni: 50 $\mu$ "Min.Overall Sn: 10~20 $\mu$ "	T=0.20
2	CONTACT	8	COPPER ALLOY	Ni: 50 $\mu$ "Min.Overall Au: 5 $\mu$ " Sn: Matte Pure Sn 100~120 $\mu$ "	T=0.30
1	HOUSING	1	THERMOPLASTIC	UL 94V-0, COLOR:BLACK	+G.F 30%



深圳市华宇创精密电子有限公司

<b>TOLERANCE:</b> X.X $\pm 0.30$ X.XX $\pm 0.25$ X.XXX $\pm 0.15$ X' $\pm 2'$ X.X' $\pm 0.5'$	<b>DRAWN BY :</b> 陈一鸣	<b>DATE :</b> 2014-02-23	<b>PART NAME:</b> RJ45 沉板上8.6
	<b>CHECKED BY:</b> 马跃	<b>DATE :</b> 2014-02-23	<b>PART NO.:</b> HYCW114-RJ45-086B
<b>UNIT:</b> mm [inch]	<b>APPROVED BY:</b>	<b>DATE :</b> 2014-02-23	<b>DRAW NO.:</b> HYC-RJ16061218
<b>SCALE:</b> 1:1 <b>SIZE:</b> A4			<b>SHEET NO.:</b> 1 OF 1