1-2199298-5 - ACTIVE

## DIPLOMATE TE Internal #: 1-2199298-5 Stamped & Formed, 18 Position, Low Profile, Through Hole, Tin, -40 – 105 °C [-40 – 221 °F], DIP Sockets

#### View on TE.com >



Connectors > Socket Connectors > IC Sockets > DIP Sockets > DIP Socket: Low Profile, Stamped & Formed, Open, Tin



Contact Fabrication: Stamped & Formed

Number of Positions: 18

Connector Profile: Low

Row-to-Row Spacing: 7.62 mm [.3 in]

Leg Style: Through Hole

All DIP Socket: Low Profile, Stamped & Formed, Open, Tin (6)

### Features

#### Product Type Features

Connector & Contact Terminates To

Lea Style

Printed Circuit Board

Through Hole

#### **Configuration Features**

Number of Rows	2			
PCB Mount Orientation	Vertical			
Number of Positions	18			
Electrical Characteristics				
Insulation Resistance	1000 MΩ			
Contact Resistance	20 mΩ			
Body Features				
Sleeve Material	Brass/Copper			
Sleeve Plating Material	Tin/Lead			
Frame Style	Ladder			
Connector Profile	Low			
Contact Features				
Mating Contact Type	Dual Leaf			

#### 1-2199298-5

Stamped & Formed, 18 Position, Low Profile, Through Hole, Tin, -40 – 105 °C [-40 – 221 °F], DIP Sockets



IC Socket Type	DIP
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Fabrication	Stamped & Formed
Contact Mating Area Plating Material	Tin
	60 µin
Contact Current Rating (Max)	1 A
Termination Features	
	3 in
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	PBT GF30
Housing Color	Black
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Profile Height from PCB	5.1 mm[.2 in]
Product Length	22.86 mm[.9 in]
Row-to-Row Spacing	7.62 mm[.3 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Tubes per Box	2
Packaging Quantity	26

#### 1-2199298-5

Stamped & Formed, 18 Position, Low Profile, Through Hole, Tin, -40 – 105 °C [-40 – 221 °F], DIP Sockets



Packaging Method	Box & Tube, Tube
Other	
Quantity per Tube	2600
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge

based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Customers Also Bought



#### 1-2199298-5

Stamped & Formed, 18 Position, Low Profile, Through Hole, Tin, -40 – 105 °C [-40 – 221 °F], DIP Sockets







### Documents

Product Drawings 18P,DIP SKT,300 CL,LDR,PB FREE

English

CAD Files 3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_1-2199298-5\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2199298-5\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-2199298-5\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages DIP Sockets Quick Reference Guide (EN)

English