

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER ECO-11-005033	02APR2011	RK	HMR
	A2	REDRAW IN TO CREO	14APR2017	GH	JP

Technical drawing of a Mini Mic SRS Tab Contact. The drawing includes a front view, a side view, and a cross-sectional view. Key dimensions are as follows:

- Front view: Total length 22.7 ±0.3 mm. Zone A length 5.6 mm. Zone B length 6.2 mm. Contact width 1.6 ±0.2 mm. Lead length 1.5 ±0.1 mm.
- Side view: Contact height 0.8 ±0.2 mm. Lead diameter 0.32 ±0.02 mm. Zone A length 10.4 ±0.2 mm. Zone B length 6.2 mm. Distance from lead to Zone A start 2 ±0.2 mm. Distance from Zone A end to Zone B start 2.6 ±0.2 mm.
- Cross-sectional view: Contact width 5.2 ±0.3 mm. Contact height 4.7 ±0.3 mm. Lead diameter 2.5 ±0.2 mm. Distance from lead to contact center 2.5 ±0.3 mm.

Two cross-sectional views, A-A and B-B, showing the internal profile of the contact. View A-A shows a width of 2.5 ±0.2 mm and a height of 2.3 ±0.3 mm. View B-B shows a width of 5.2 ±0.3 mm and a height of 4.7 ±0.3 mm.

1 GOLD PLATED 0.8 μm OVER "ZONE A". TIN PLATED OVER "ZONE B" AND NICKEL UNDERPLATING ALL OVER. DORATURA 0.8 μm NELLA "ZONA A". STAGNATURA NELLA "ZONA B" E NICHELATURA SU TUTTO IL CONTATTO.

2 SUITABLE FOR SINGLE WIRE SEAL TE P/N 281934-4 ADATTO PER GOMMINO PASSACAVO TE P/N 281934-4

A2 3 ITEM IS SUPPLIED REELED ON CARTON REEL WITH STRIP PITCH = 11.9 ±0.1mm STATO DI FORNITURA: AVVOLTI SU BOBINA CON PASSO TRA TERMINALI DI = 11.9 ±0.1mm

INS. DIA. RANGE (DIAM. ISOLANTE)	WIRE RANGE (RANGO FILO)
2	Ø0.35 - 0.5mm ²

DIRECTION OFF TOP OF REEL
SENSO DI USCITA DALLA BOBINA

Diagram showing the direction of the reel, with an arrow indicating the direction of travel.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC ±
	1 PLC ±
	2 PLC ± ±0.3
	3 PLC ±
	4 PLC ±
	ANGLES ±2°
MATERIAL	FINISH
-	-
-	-

DWN	C.BERTINI	JUN1992
CHK	A.BRUNI	JUN1992
APVD	-	-
PRODUCT SPEC	108-20090	
APPLICATION SPEC	114-20045	
WEIGHT	-	
CUSTOMER DRAWING		

GOLD PLTD (DORATO) 1		BRASS (OTTONE)	282404-3	A
PRE-TIN (PRE STAGNATO)		BRASS (OTTONE)	282404-1	A
FINISH/COLOUR (FINITURA/COLORE)		MATERIAL (MATERIALE)	TE PART NO. (NUMERO)	REV
STE TE Connectivity				
NAME: MINI MIC SRS TAB CONTACT				
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
A3	00779	©=282404	-	
SCALE: 5:1			SHEET: 1 OF 1	REV: A2

1470-19 (3/13)