

METRIC		LOC	DIST	REVISIONS				DATE	DWN	APVD
		I	—	P	LTR	REV	DESCRIPTION	DATA	DIS.	APP.
					A	4	REVISED PER ECR-14-005556	16JUL2014	M.G.	M.G.

1) ADATTO PER GOMMINO TE P/N 281934-...
(SUITABLE FOR SINGLE WIRE SEAL TE P/N 281934-...)

2) MASSIMA CORRENTE 14A
(MAX. CURRENT 14A)

PRE STAGNATO (PRE-TINNED)	BRONZO FOSFOROSO (PH. BRONZE)	282466-1
FINITURA / COLORE (FINISH / COLOUR)	MATERIALE (MATERIAL)	NUMERO (PART NUMBER)

DIAM. ISOLANTE (INS. DIA. RANGE)	RANGO FILO (WIRE RANGE)	CUSTOMER DWG. FOR REFERENCE ONLY		DISEGNO PER CLIENTE SOLO PER RIFERIMENTO	
VED. NOTA 1) (SEE NOTE 1))	1.5-2.5mm ²				

DIMENSIONS: DIMENSIONI: mm	DWN / DIS. BERTINI 12 DEC.92	MATERIAL MATERIALE	FINISH FINITURA
TOLERANCES UNLESS OTHERWISE SPECIFIED: TOLLERANZE: SE NON DIVERSAMENTE SPECIFICATO	CHK / CONT. A. BRUNI 12 DEC '92	TE Connectivity	
0 PLC / DEC: ± — 1 PLC / DEC: ± 0.3 2 PLC / DEC: ± — 3 PLC / DEC: ± — 4 PLC / DEC: ± — ANGLES / ANGOLI ± 2°	APVD / APP. —	NAME NOME	
	PRODUCT SPEC SPEC DI PRODOTTO	MINI MIC SRS REC. CONTACT	
	APPLICATION SPEC SPEC DI APPLICAZIONE	SIZE	RESTRICTED TO
	114-20045	CAGE CODE	—
	WEIGHT PESO	DRAWING NO NUMERO	
	—	A4 00779	
CUSTOMER DRAWING		C-282466	

SCALE SCALA	SHEET FOGLIO	REV
5:1	1 OF 1	A4