



CONTACT IS PLATED OVERALL WITH .000050 NICKEL, THEN .000030 GOLD OVER CONTACT LENGTH INDICATED AND TIN PLATED ON SOLDER TAIL END.

Inputs and copy not to be re-used or published without written permission of JPL's Director

RECOMMENDED LAYOUT
FOR .062 THICK P.C. BOARD

350214

QTY		REV	DATE	DESCRIPTION	NUMBER	NAME	REMARKS	ITEM NO.
REQUIRED PER ASSEMBLY					© 1978 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.			CUSTOMER COPY REFERENCE ONLY
OR <i>[Signature]</i> 3/2/73 CHL <i>[Signature]</i> 3/2/73 ENR/DL/TOR/WHS					MATERIAL AND FINISH		 TE Connectivity	
					SEE TABLE			
DE <i>[Signature]</i> 4-8-73 APP					WIDE - RANGE - INSULATION		GLASS	
					TOLERANCE EXCEPT AS NOTED		TYPE	
DESCRIPTION					SCALE	LOC	NO.	REV
<i>[Signature]</i> 4-8-73					1/8" = 1/4"	CM B	350214	P2
					NAME 16 CIRCUIT MATE-N-LOK P.C. BOARD HEADER			