



SPECIFICATIONS:

- Current Rating: 3A AC,DC
- Voltage Rating: 250V AC,DC
- Temperature Range: -40°C ~ +105°C
- Contact Resistance: 30mΩ Max
- Insulation Resistance: 1000MΩ Min
- Withstanding Voltage: 1000V AC/minute
- Pin Material: Brass/Tin-Plated
- Material: Nylon 66,UL94V-0(White)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x3P	4.00	8.00	6.80	2x12P	22.00	26.00	24.80
2x4P	6.00	10.00	8.80	2x13P	24.00	28.00	26.80
2x5P	8.00	12.00	10.80	2x14P	26.00	30.00	28.80
2x6P	10.00	14.00	12.80	2x15P	28.00	32.00	30.80
2x7P	12.00	16.00	14.80	2x16P	30.00	34.00	32.80
2x8P	14.00	18.00	16.80	2x17P	32.00	36.00	34.80
2x9P	16.00	20.00	18.80	2x18P	34.00	38.00	36.80
2x10P	18.00	22.00	20.80	2x19P	36.00	40.00	38.80
2x11P	20.00	24.00	22.80	2x20P	38.00	42.00	40.80



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	3:1	1 of 1

Title :
2.00mm PITCH
180° WAFER

Draw BY:	Approved :
LIZQ	GONGYB

General Tolerance

x.xx±0.25	ANGLE±
x.xxx±0.20	
x.xxxx±0.15	

DRAW NO : **A2008WV-2xXP** REV **A0**

A0	NEW RELEEASE	2009.05.10
REV	DESCRIPTION	DATE