


# IRLML9301TRPbF

HEXFET® Power MOSFET

|                                                              |             |           |
|--------------------------------------------------------------|-------------|-----------|
| <b>V<sub>DS</sub></b>                                        | <b>-30</b>  | <b>V</b>  |
| <b>V<sub>GS</sub> Max</b>                                    | <b>± 20</b> | <b>V</b>  |
| <b>R<sub>DS(on)</sub> max</b><br>(@ V <sub>GS</sub> = -10V)  | <b>64</b>   | <b>mΩ</b> |
| <b>R<sub>DS(on)</sub> max</b><br>(@ V <sub>GS</sub> = -4.5V) | <b>103</b>  | <b>mΩ</b> |



## Application(s)

- System/Load Switch

## Features and Benefits

### Features

|                                                              |
|--------------------------------------------------------------|
| Low R <sub>DS(on)</sub> ( ≤ 64mΩ)                            |
| Industry-standard pinout                                     |
| Compatible with existing Surface Mount Techniques            |
| RoHS compliant containing no lead, no bromide and no halogen |
| MSL1, Consumer qualification                                 |

results in  
⇒

### Benefits

|                            |
|----------------------------|
| Lower switching losses     |
| Multi-vendor compatibility |
| Easier manufacturing       |
| Environmentally friendly   |
| Increased reliability      |

| Symbol                                 | Parameter                                       | Max.         | Units |
|----------------------------------------|-------------------------------------------------|--------------|-------|
| V <sub>DS</sub>                        | Drain-Source Voltage                            | -30          | V     |
| I <sub>D</sub> @ T <sub>A</sub> = 25°C | Continuous Drain Current, V <sub>GS</sub> @ 10V | -3.6         | A     |
| I <sub>D</sub> @ T <sub>A</sub> = 70°C | Continuous Drain Current, V <sub>GS</sub> @ 10V | -2.9         |       |
| I <sub>DM</sub>                        | Pulsed Drain Current                            | -15          |       |
| P <sub>D</sub> @ T <sub>A</sub> = 25°C | Maximum Power Dissipation                       | 1.3          | W     |
| P <sub>D</sub> @ T <sub>A</sub> = 70°C | Maximum Power Dissipation                       | 0.8          |       |
|                                        | Linear Derating Factor                          | 0.01         | W/°C  |
| V <sub>GS</sub>                        | Gate-to-Source Voltage                          | ± 20         | V     |
| T <sub>J</sub> , T <sub>STG</sub>      | Junction and Storage Temperature Range          | -55 to + 150 | °C    |

## Thermal Resistance

| Symbol           | Parameter                     | Typ. | Max. | Units |
|------------------|-------------------------------|------|------|-------|
| R <sub>θJA</sub> | Junction-to-Ambient ③         | —    | 100  | °C/W  |
| R <sub>θJA</sub> | Junction-to-Ambient (t<10s) ④ | —    | 99   |       |

## ORDERING INFORMATION:

See detailed ordering and shipping information on the last page of this data sheet.


Notes ① through ④ are on page 10  
www.irf.com

**Electric Characteristics @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**


| Symbol                          | Parameter                            | Min. | Typ. | Max. | Units               | Conditions                                            |
|---------------------------------|--------------------------------------|------|------|------|---------------------|-------------------------------------------------------|
| $V_{(BR)DSS}$                   | Drain-to-Source Breakdown Voltage    | -30  | —    | —    | V                   | $V_{GS} = 0V, I_D = -250\mu A$                        |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient  | —    | 0.02 | —    | V/ $^\circ\text{C}$ | Reference to $25^\circ\text{C}$ , $I_D = -1\text{mA}$ |
| $R_{DS(on)}$                    | Static Drain-to-Source On-Resistance | —    | 51   | 64   | $m\Omega$           | $V_{GS} = -10V, I_D = -3.6A$ ②                        |
|                                 |                                      | —    | 82   | 103  |                     | $V_{GS} = -4.5V, I_D = -2.9A$ ②                       |
| $V_{GS(th)}$                    | Gate Threshold Voltage               | -1.3 | —    | -2.4 | V                   | $V_{DS} = V_{GS}, I_D = -10\mu A$                     |
| $I_{DSS}$                       | Drain-to-Source Leakage Current      | —    | —    | 1    | $\mu A$             | $V_{DS} = -24V, V_{GS} = 0V$                          |
|                                 |                                      | —    | —    | 150  |                     | $V_{DS} = -24V, V_{GS} = 0V, T_J = 125^\circ\text{C}$ |
| $I_{GSS}$                       | Gate-to-Source Forward Leakage       | —    | —    | -100 | nA                  | $V_{GS} = -20V$                                       |
|                                 | Gate-to-Source Reverse Leakage       | —    | —    | 100  |                     | $V_{GS} = 20V$                                        |
| $R_G$                           | Internal Gate Resistance             | —    | 12   | —    | $\Omega$            |                                                       |
| $g_{fs}$                        | Forward Transconductance             | 5.0  | —    | —    | S                   | $V_{DS} = -10V, I_D = -3.6A$                          |
| $Q_g$                           | Total Gate Charge                    | —    | 4.8  | —    | nC                  | $I_D = -3.6A$                                         |
| $Q_{gs}$                        | Gate-to-Source Charge                | —    | 1.2  | —    |                     | $V_{DS} = -15V$                                       |
| $Q_{gd}$                        | Gate-to-Drain ("Miller") Charge      | —    | 2.5  | —    |                     | $V_{GS} = -4.5V$ ②                                    |
| $t_{d(on)}$                     | Turn-On Delay Time                   | —    | 9.6  | —    | ns                  | $V_{DD} = -15V$ ②                                     |
| $t_r$                           | Rise Time                            | —    | 19   | —    |                     | $I_D = -1A$                                           |
| $t_{d(off)}$                    | Turn-Off Delay Time                  | —    | 16   | —    |                     | $R_G = 6.8\Omega$                                     |
| $t_f$                           | Fall Time                            | —    | 15   | —    |                     | $V_{GS} = -4.5V$                                      |
| $C_{iss}$                       | Input Capacitance                    | —    | 388  | —    | pF                  | $V_{GS} = 0V$                                         |
| $C_{oss}$                       | Output Capacitance                   | —    | 93   | —    |                     | $V_{DS} = -25V$                                       |
| $C_{rss}$                       | Reverse Transfer Capacitance         | —    | 65   | —    |                     | $f = 1.0\text{KHz}$                                   |

**Source - Drain Ratings and Characteristics**


| Symbol   | Parameter                                 | Min. | Typ. | Max. | Units | Conditions                                                              |
|----------|-------------------------------------------|------|------|------|-------|-------------------------------------------------------------------------|
| $I_S$    | Continuous Source Current<br>(Body Diode) | —    | —    | -1.3 | A     | MOSFET symbol<br>showing the<br>integral reverse<br>p-n junction diode. |
| $I_{SM}$ | Pulsed Source Current<br>(Body Diode) ①   | —    | —    | -15  |       |                                                                         |
| $V_{SD}$ | Diode Forward Voltage                     | —    | —    | -1.2 | V     | $T_J = 25^\circ\text{C}, I_S = -1.3A, V_{GS} = 0V$ ②                    |
| $t_{rr}$ | Reverse Recovery Time                     | —    | 14   | 21   | ns    | $T_J = 25^\circ\text{C}, V_R = -24V, I_F = -1.3A$                       |
| $Q_{rr}$ | Reverse Recovery Charge                   | —    | 7.2  | 11   | nC    | $di/dt = 100A/\mu s$ ②                                                  |




**Fig 1.** Typical Output Characteristics




**Fig 2.** Typical Output Characteristics




**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Normalized On-Resistance Vs. Temperature




**Fig 5.** Typical Capacitance Vs. Drain-to-Source Voltage




**Fig 6.** Typical Gate Charge Vs. Gate-to-Source Voltage




**Fig 7.** Typical Source-Drain Diode Forward Voltage




**Fig 8.** Maximum Safe Operating Area




**Fig 9.** Maximum Drain Current Vs. Ambient Temperature




**Fig 10a.** Switching Time Test Circuit




**Fig 10b.** Switching Time Waveforms




**Fig 11.** Typical Effective Transient Thermal Impedance, Junction-to-Ambient




**Fig 12.** Typical On-Resistance Vs. Gate Voltage




**Fig 13.** Typical On-Resistance Vs. Drain Current




**Fig 14a.** Gate Charge Waveform



**Fig 14b.** Gate Charge Test Circuit



**Fig 15.** Typical Threshold Voltage Vs. Junction Temperature




**Fig 16.** Typical Power Vs. Time

# IRLML9301TRPbF

International  
**IR** Rectifier

## Micro3 (SOT-23) Package Outline

Dimensions are shown in millimeters (inches)




| DIMENSIONS |             |      |        |       |
|------------|-------------|------|--------|-------|
| SYMBOL     | MILLIMETERS |      | INCHES |       |
|            | MIN         | MAX  | MIN    | MAX   |
| A          | 0.89        | 1.12 | 0.035  | 0.044 |
| A1         | 0.01        | 0.10 | 0.0004 | 0.004 |
| A2         | 0.88        | 1.02 | 0.035  | 0.040 |
| b          | 0.30        | 0.50 | 0.012  | 0.020 |
| c          | 0.08        | 0.20 | 0.003  | 0.008 |
| D          | 2.80        | 3.04 | 0.110  | 0.120 |
| E          | 2.10        | 2.64 | 0.083  | 0.104 |
| E1         | 1.20        | 1.40 | 0.047  | 0.055 |
| e          | 0.95        | BSC  | 0.037  | BSC   |
| e1         | 1.90        | BSC  | 0.075  | BSC   |
| L          | 0.40        | 0.60 | 0.016  | 0.024 |
| L1         | 0.54        | REF  | 0.021  | REF   |
| L2         | 0.25        | BSC  | 0.010  | BSC   |
| Ø          | 0           | 8    | 0      | 8     |

1. DIMENSIONING & TOLERANCING PER ANSI Y14.5M-1994
2. DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES)
3. CONTROLLING DIMENSION: MILLIMETER
4. DATUM PLANE H IS LOCATED AT THE MOLD PARTING LINE
5. DATUM A AND B TO BE DETERMINED AT DATUM PLANE H
6. DIMENSIONS D AND E1 ARE MEASURED AT DATUM PLANE H. DIMENSIONS DOES NOT INCLUDE MOLD PROTRUSIONS OR INTERLEAD FLASH. MOLD PROTRUSIONS OR INTERLEAD FLASH SHALL NOT EXCEED 0.25 MM (0.010 INCH) PER SIDE
7. DIMENSION L IS THE LEAD LENGTH FOR SOLDERING TO A SUBSTRATE
8. OUTLINE CONFORMS TO JEDEC OUTLINE TO-236 AB

## Micro3 (SOT-23/TO-236AB) Part Marking Information

Notes: This part marking information applies to devices produced after 02/26/2001



Note: A line above the work week (as shown here) indicates Lead-Free.

### DATE CODE MARKING INSTRUCTIONS

WW = (1-26) IF PRECEDED BY LAST DIGIT OF CALENDAR YEAR

| YEAR | Y    | WORK WEEK | W |
|------|------|-----------|---|
| 2011 | 2001 | 01        | A |
| 2012 | 2002 | 02        | B |
| 2013 | 2003 | 03        | C |
| 2014 | 2004 | 04        | D |
| 2015 | 2005 | 05        |   |
| 2016 | 2006 | 06        |   |
| 2017 | 2007 | 07        |   |
| 2018 | 2008 | 08        |   |
| 2019 | 2009 | 09        |   |
| 2020 | 2010 | 24        | X |
|      |      | 25        | Y |
|      |      | 26        | Z |


WW = (27-52) IF PRECEDED BY A LETTER

| YEAR | Y    | WORK WEEK | W |
|------|------|-----------|---|
| 2011 | 2001 | A 27      | A |
| 2012 | 2002 | B 28      | B |
| 2013 | 2003 | C 29      | C |
| 2014 | 2004 | D 30      | D |
| 2015 | 2005 | E         |   |
| 2016 | 2006 | F         |   |
| 2017 | 2007 | G         |   |
| 2018 | 2008 | H         |   |
| 2019 | 2009 | J         |   |
| 2020 | 2010 | K 50      | X |
|      |      | 51        | Y |
|      |      | 52        | Z |

Note: For the most current drawing please refer to IR website at: <http://www.irf.com/package/>

## Micro3™ (SOT-23) Tape & Reel Information

Dimensions are shown in millimeters (inches)



- NOTES:
1. CONTROLLING DIMENSION : MILLIMETER.
  2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Note: For the most current drawing please refer to IR website at: <http://www.irf.com/package/>  
www.irf.com

# IRLML9301TRPbF

International  
**IR** Rectifier

| Orderable part number | Package Type    | Standard Pack |          | Note |
|-----------------------|-----------------|---------------|----------|------|
|                       |                 | Form          | Quantity |      |
| IRLML9301TRPbF        | Micro3 (SOT-23) | Tape and Reel | 3000     |      |

## Qualification information<sup>†</sup>

|                            |                                                                          |                                                    |
|----------------------------|--------------------------------------------------------------------------|----------------------------------------------------|
| Qualification level        | Consumer <sup>††</sup><br>(per JEDEC JESD47F <sup>†††</sup> guidelines ) |                                                    |
| Moisture Sensitivity Level | Micro3 (SOT-23)                                                          | MSL1<br>(per IPC/JEDEC J-STD-020D <sup>†††</sup> ) |
| RoHS compliant             | Yes                                                                      |                                                    |

† Qualification standards can be found at International Rectifier's web site

<http://www.irf.com/product-info/reliability>

†† Higher qualification ratings may be available should the user have such requirements.

Please contact your International Rectifier sales representative for further information:

<http://www.irf.com/whoto-call/salesrep/>

††† Applicable version of JEDEC standard at the time of product release.

## Notes:

① Repetitive rating; pulse width limited by max. junction temperature.

② Pulse width ≤ 400μs; duty cycle ≤ 2%.

③ Surface mounted on 1 in square Cu board

④ Refer to [application note #AN-994](#).

Data and specifications subject to change without notice.

International  
**IR** Rectifier

IR WORLD HEADQUARTERS: 101N.Sepulveda blvd, El Segundo, California 90245, USA Tel: (310) 252-7105

TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.02/2012

[www.irf.com](http://www.irf.com)

## IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office ([www.infineon.com](http://www.infineon.com)).

## WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.