





SMD Power Inductor CDRH2D16/LD




Dimension - [mm]



Land pattern and Schematics - [mm]



(2.2 μ H~4.7 μ H)



(5.6 μ H~27 μ H)

Description

- Ferrite drum core construction.
- Magnetically shielded.
- L × W × H: 3.2 × 3.2 × 1.8mm Max.
- Product weight: 60mg(Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.

Environmental Data

- Operating temperature range: -40°C~+100°C (including coil's self temperature rise)
- Storage temperature range: -40°C~+100°C
- Solder reflow temperature: 260 °C peak.

Packaging

- Carrier tape and reel packaging
- 7.0" diameter reel
- 1000pcs per reel

Applications

- Ideally used in Mobilephone, PDA, MP3, DSC/DVC, etc. as DC-DC converter inductors.

SMD Power Inductor

CDRH2D16/LD



Electrical Characteristics

Part Name	Stamp	Inductance (μ H) [within] ※1	D.C.R. (m Ω) Max. (Typ.) (at 20°C)	Saturation Current (A) ※2		Temperature Rise Current (A) ※3
				at 20°C	at 100°C	
CDRH2D16LDNP-2R2NC	A	$2.2 \pm 30\%$	47(38)	0.86	0.65	2.20
CDRH2D16LDNP-2R7NC	B	$2.7 \pm 30\%$	61(49)	0.82	0.60	1.90
CDRH2D16LDNP-3R3NC	C	$3.3 \pm 30\%$	67(54)	0.72	0.52	1.74
CDRH2D16LDNP-3R9NC	D	$3.9 \pm 30\%$	75(60)	0.70	0.48	1.60
CDRH2D16LDNP-4R7NC	E	$4.7 \pm 30\%$	101(81)	0.62	0.45	1.32
CDRH2D16LDNP-5R6NC	F	$5.6 \pm 30\%$	123(98)	0.57	0.40	1.25
CDRH2D16LDNP-6R8NC	G	$6.8 \pm 30\%$	158(127)	0.50	0.35	1.00
CDRH2D16LDNP-8R2NC	H	$8.2 \pm 30\%$	171(137)	0.45	0.33	0.95
CDRH2D16LDNP-100NC	I	$10.0 \pm 30\%$	195(156)	0.42	0.30	0.92
CDRH2D16LDNP-120NC	J	$12.0 \pm 30\%$	223(179)	0.39	0.28	0.85
CDRH2D16LDNP-150NC	K	$15.0 \pm 30\%$	248(198)	0.35	0.26	0.81
CDRH2D16LDNP-180NC	L	$18.0 \pm 30\%$	316(252)	0.32	0.23	0.73
CDRH2D16LDNP-220NC	M	$22.0 \pm 30\%$	418(335)	0.28	0.21	0.60
CDRH2D16LDNP-270NC	N	$27.0 \pm 30\%$	466(373)	0.26	0.18	0.53

※1 Inductance measuring condition: at 100 kHz.

※2 Saturation current: The DC current at which the inductance decreases to 65% of it's nominal value.













※3 Temperature rise current: The DC current at which the temperature rise is $\Delta T = 40^\circ\text{C}$. ($T_a = 20^\circ\text{C}$)

SMD Power Inductor CDRH2D16/LD



Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT





SMD Power Inductor CDRH2D16/LD




Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT




Solder Reflow Condition

Heat Endurance



Temperature Chart



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)

Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Obernzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com