




SPECIFICATION

- 规格  
 1 Rating : DC 12V 3A;  
 1. 额定值: DC 12V 3A;  
 2 Contact resistance: <0.03Ω;  
 2 接触电阻: <0.03Ω;  
 3 Insulation resistance: 100MΩ (DC250V);  
 3 绝缘电阻: 100MΩ (DC250V);  
 4 Withstand voltage: 500VAC;  
 4 耐压: 500VAC;  
 5 Insertion and extraction force: 5-30N;  
 5 插拔力: 5-30N;  
 6 life test: 5 000 cycles.  
 6 寿命试验: 5 000次循环  
 7 PLUG 插入后上下左右4个方向无断现象



SECTION B-B



SECTION A-A

	MATERIAL	PLATING
center pin	Brass	ag
coat	Phosphor Bronze	ni
terminal 2	Phosphor Bronze	ag
plastic	Lcp	

广东星坤科技股份有限公司

生效日期

文件工程章

MARK	DESCRIPTION	REVISIONS	DATE	REVISED	APPROVED

UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO.:
APPD		DATE		SIZE: A4	DC-042F-3A-1.65
				XKB INDUSTRIAL PRECISION CO.,LIMITED	WEIGHT 1.0g
					SHEET 1/1
					REVISION A0