



400W LOW CLAMPING VOLTAGE SINGLE TVS FOR PROTECTION


This TVS/Zener Series has been designed to Protect Sensitive Equipment against ESD and to prevent Latch-Up events in very sensitive CMOS circuitry operating at 5V, 12V, 15V and 24Vdc. These devices come in an industry standard SOD123 package making them suitable for Portable/Computing Electronics, where the board space is a premium.

SPECIFICATION FEATURES

- 400W Power Dissipation (8/20 μ s Waveform)
- Very Low Leakage Current
- IEC61000-4-2 ESD 15kV air, 8kV Contact Compliance
- SOD123 Package
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)

APPLICATIONS

- Personal Digital Assistant (PDA)
- Digital Cameras
- Portable Instrumentation
- Mobile Phones and Accessories
- Desktops, Laptops



MAXIMUM RATINGS

Rating	Symbol	Value	Units
Peak Pulse Power (8/20 μ s Waveform)	P_{pp}	400	W
ESD Voltage (HBM)	V_{ESD}	25	kV
Operating Temperature Range	T_J	-55 to +125	$^{\circ}$ C
Storage Temperature Range	T_{stg}	-55 to +150	$^{\circ}$ C

ELECTRICAL CHARACTERISTICS $T_J = 25^{\circ}$ C

PJSD05 Marking T1S

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				5	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1 \text{ mA}$	6.0			V
Reverse Leakage Current	I_R	$V_R = 5 \text{ V}$			20	μ A
Clamping Voltage (8/20 μ s)	V_C	$I_{pp} = 5 \text{ A}$			7.5	V
Clamping Voltage (820 μ s)	V_C	$I_{pp} = 24 \text{ A}$			16	V
Off State Junction Capacitance	C_j	0 Vdc Bias $f = 1 \text{ MHz}$			550	pF
Off State Junction Capacitance	C_j	5 Vdc Bias $f = 1 \text{ MHz}$			235	pF

**ELECTRICAL CHARACTERISTICS** $T_j = 25^{\circ}\text{C}$ **PJSD12 Marking T4S**

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				12	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1\text{mA}$	13.3			V
Reverse Leakage Current	I_R	$V_R = 12\text{V}$			1	μA
Clamping Voltage (8/20 μs)	V_c	$I_{pp} = 5\text{A}$			14.5	V
Clamping Voltage (8/20 μs)	V_c	$I_{pp} = 17\text{A}$			23	V
Off State Junction Capacitance	C_j	0 Vdc Bias $f = 1\text{MHz}$			180	pF

PJSD15 Marking T5S





Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				15	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1\text{mA}$	16.7			V
Reverse Leakage Current	I_R	$V_R = 15\text{V}$			1	μA
Clamping Voltage (8/20 μs)	V_c	$I_{pp} = 5\text{A}$			19	V
Clamping Voltage (8/20 μs)	V_c	$I_{pp} = 14\text{A}$			28	V
Off State Junction Capacitance	C_j	0 Vdc Bias $f = 1\text{MHz}$			165	pF

PJSD24 Marking T6S

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				24	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1\text{mA}$	26.7			V
Reverse Leakage Current	I_R	$V_R = 24\text{V}$			1	μA
Clamping Voltage (8/20 μs)	V_c	$I_{pp} = 5\text{A}$			29	V
Clamping Voltage (8/20 μs)	V_c	$I_{pp} = 11\text{A}$			37	V
Off State Junction Capacitance	C_j	0 Vdc Bias $f = 1\text{MHz}$			120	pF




TYPICAL CHARACTERISTICS



PACKAGE DIMENSIONS AND BOND PAD LAYOUT


SOD-123

Unit : inch(mm)



SOD-123

Unit : inch(mm)



PJSD05 SERIES

Part No_packing code_Version

PJSD05_R1_00001

PJSD05_R2_00001

For example :

RB500V-40_R2_00001

Part No.

Serial number

Version code means HF

Packing size code means 13"

Packing type means T/R

Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



PJSD05 SERIES

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.