

Low-profile Master Type (Slim Type) RS**N11S Series

- [Photo](#) |
 [Dimensions](#) |
 [Mounting Hole Dimensions](#) |
 [Terminal Layout / Circuit Diagram](#) |
 [Packing Specifications](#) |
 [Soldering Conditions](#)

PRINT


Part number	RS60N11S4006	
Number of resistor elements	Single-unit	
Direction of lever	Vertical	
Travel	60mm	
Lever type	4	
Length of lever	20mm	
Total resistance	10kΩ	
Resistance taper	1B	
Terminal style	For PC board	
Operating temperature range	-10°C to +60°C	
Electrical performance	Total resistance tolerance	±20%
	Maximum operating voltage	200V AC, 10V DC
	Rated power	0.2W
	Insulation resistance	100MΩ min. 250V DC
	Voltage proof	250V AC for 1 minute
Mechanical performance	Operating force	0.3(+0.5, -0.25)N
	Stopper strength	100N
	Lever push-pull strength	50N
	Lever wobble (Both side)	3.2mm
	Lever deviation (One side)	0.5mm max.
Durability	Operating life	30,000 cycles
Minimum order unit (pcs.)	Japan	600
	Export	1,200




Photo



Dimensions




Mounting Hole Dimensions



Viewed from mounting side.

Terminal Layout / Circuit Diagram



Packing Specifications

Tray

Number of packages (pcs.) 1 case / Japan 600

1 case / export packing 1,200

Export package measurements (mm) 377×517×371

Soldering Conditions

Reference for Dip Soldering

Preheating Soldering surface temperature 100° max.

Heating time 1 min. max.

Dip soldering Soldering temperature 260° max.

Soldering time 5s max.

No. of solders 1 time

Reference for Hand Soldering

Tip temperature 350° max.

Soldering time 3s max.

No. of solders 1 time

Notes are common to this series/models.

1. This site catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
2. Please place purchase orders per minimum order unit (integer).
3. Products other than those listed in above products are also available. Please contact us for details.
4. "L" in the "Lever Wobble" column of the above table indicates the length of lever.

Inquiries about Products

 [Inquiry](#)