




N-Ch and P-Ch MOSFETS
General Description

-40V /-6A Single P Power MOSFET
 Very low on-resistance $R_{DS(on)}$ @ $V_{GS}=4.5$ V
 Pb-free lead plating; RoHS compliant

V_{DS}	-40	V
$R_{DS(on),TYP@V_{GS}=10V}$	44.1	m Ω
$R_{DS(on),TYP@V_{GS}=4.5}$	69.3	m Ω
I_D	-6	A



Part ID	Package Type	Marking	Tape and reel information
SM4614BPRL	SOP8	4614B	3000



100% UIS Tested
 100% Kg Tested

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	V_{DS}	-40	V
Gate-Source Voltage	V_{GS}	20	\pm V
Continuous Drain Current ^A	I_D	$T_A=25^\circ\text{C}$	A
		$T_A=70^\circ\text{C}$	
Pulsed Drain Current ^B	I_{DM}	-9.6	
Avalanche Current ^G	I_{AR}	-1.9	
Repetitive avalanche energy $L=0.1\text{mH}$ ^G	E_{AR}	-4.4	mJ
Power Dissipation ^A	P_D	$T_A=25^\circ\text{C}$	W
		$T_A=70^\circ\text{C}$	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	$R_{\theta JA}$	157	236	$^\circ\text{C/W}$
Maximum Junction-to-Ambient ^A		Steady State	315	378
Maximum Junction-to-Lead ^c	$R_{\theta JL}$	94	151	$^\circ\text{C/W}$



STATIC PARAMETERS

Symbol	Parameter	Conditions	Min	Typ	Max	Units
BV _{DSS}	Drain-Source Breakdown Voltage	I _D = -250uA, V _{GS} = 0V	-40			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-40V, V _{GS} =0V			-1 -5	uA
I _{GSS}	Gate-Body leakage current	V _{DS} = 0V, V _{GS} = ±20V			±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} I _D = 250µA	-1.3	-2	-2.6	V
R _{DS(ON)}	Static Drain-Source On-Resistance	V _{GS} =-10V, I _D =-6A		44.1	63.0	mΩ
		V _{GS} =-4.5V, I _D =-6A		69.3	90.1	
g _{FS}	Forward Transconductance	V _{DS} =-5V, I _D =-6A		46		S
V _{SD}	Diode Forward Voltage	I _S =-1A, V _{GS} =0V		-0.72	-1	V
I _S	Maximum Body-Diode Continuous Current				-6	A

DYNAMIC PARAMETERS

Symbol	Parameter	Conditions	Min	Typ	Max	Units
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =-15V, f=1MHz		940	1146	pF
C _{oss}	Output Capacitance			97	119	pF
C _{rss}	Reverse Transfer Capacitance			72	85	pF
R _g	Gate resistance	V _{GS} =0V, V _{DS} =0V, f=1MHz			2.15	Ω

SWITCHING PARAMETERS

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Q _g (10V)	Total Gate Charge	V _{GS} =-10V, V _{DS} =-15V, I _D =-6A		8.4		nC
Q _g 4.5V)	Total Gate Charge			4.2		
Q _{gs}	Gate Source Charge			3.01		
Q _{gd}	Gate Drain Charge			4.3		
t _{D(on)}	Turn-On DelayTime	V _{GS} =-10V, V _{DS} =-15V, R _L =0.75 Ω, R _{GEN} =3Ω		8.5		ns
t _r	Turn-On Rise Time			6.8		
t _{D(off)}	Turn-Off DelayTime			23.8		
t _f	Turn-Off Fall Time			7.65		
t _{rr}	Body Diode Reverse Recovery Time	I _F =-8A, dI/dt=500A/µs		17		ns
Q _{rr}	Body Diode Reverse Recovery Charge	I _F =18A, dI/dt=500A/µs		11.5		nC

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 10: Maximum Forward Biased Safe Operating Area (Note F)




Figure 11: Single Pulse Power Rating Junction-to-Ambient (Note F)




Figure 12: Normalized Maximum Transient Thermal Impedance (Note F)