

A759, Polymer Aluminum, 440 uF, 20%, 50 VDC, -55/+125°C, Lead Spacing = 5mm

**Dimensions**

D	10mm +/-0.5mm
L	18mm +/-2mm
S	5mm +/-0.5mm
LL Negative	15mm MIN
LL Positive	19mm MIN
F	0.6mm +/-0.05mm

**Packaging Specifications**

Packaging:	Bulk, Bag
Packaging Quantity:	250

**General Information**

Series:	A759
Dielectric:	Polymer Aluminum
Description:	Single Ended, Polymer Aluminum
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No

**Specifications**

Capacitance:	440 uF
Capacitance Tolerance:	20%
Voltage DC:	50 VDC, 57.5 VDC (Surge)
Temperature Range:	-55/+125°C
Rated Temperature:	125°C
Life:	2000 Hrs (+/-20% Initial Capacitance, 1.5x DF MAX, Leakage Within Limit)
Dissipation Factor:	12% 120Hz 20C
Resistance:	28 mOhms (100kHz 20C)
Ripple Current:	6010 mAmps (100kHz 105C), 3500 mAmps (100kHz 125C)
Leakage Current:	3300 uA (2min 20°C)