

Product Search Data Sheet

I Toddol Ocaron Dala

Note: This datasheet may be out of date. Please download the latest datasheet of NCU15WF104F6SRC from the official website of Murata Manufacturing


Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU15WF104F6SRC

# NCU15WF104F6SRC

In Production Recommended RoHS REACH AEC-

#### Appearance & Shape





## Applications

Limited Usage	Automotive Grade
Other Usage	<ol> <li>Various engine control units</li> <li>ABS control unit</li> <li>High power devices (IGBT)</li> <li>Temperature compensation for various circuits required high temperature.</li> </ol>

### Packaging Information

Packaging	Specifications	Minimum Order Quantity
RC	180mm Paper Tape	10000



Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Lead is not contained in the product.

6. NCU series are recognized by UL/cUL (UL1434, File No.E137188).



Product Search Data Sheet

NCU15WF104F6SRC

Note: This datasheet may be out of date

Please download the latest datasheet of NCU15WF104F6SRC from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU15WF104F6SRC

#### Specifications

Resistance (25°C)	100κΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	4250K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C)(Reference Value)	4303K
B-Constant(25/85°C)(Reference Value)	4311K
B-Constant(25/100°C)(Reference Value)	4334K
Max. Voltage	5V
Maximum Operating Current (25°C)	0.032mA
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40°C to 150°C
Size Code (in mm)	1.0x0.5mm
Size Code (in inch)	0.4x0.2inch
Shape	SMD
Mass	0.0012g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet




### NCU15WF104F6SRC


Note: This datasheet may be out of date.

Please download the latest datasheet of NCU15WF104F6SRC from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=NCU15WF104F6SRC







**Resistance-Temperature Characteristics** 

Maximum Operating Voltage Reduction Characteristics

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

3 of 3