

Unshielded Drum Core Inductor

PA4306.XXXNL, PA4307.XXXNL & PA4308.XXXNL Series



- Height:** 3.1mm (PA4306), 3.5mm (PA4307) and 4.8mm (PA4308) Max
- Footprint:** 7.3 x 7.3 mm Max
- Current Rating:** 0.22A to 12A
- Inductance Range:** 1uH to 1000uH

Electrical Specifications @ 25°C – Operating Temperature -40°C to 125°C

| Pulse Part Number | Inductance (uH) ^{1,2} | Rated Current (A) Max ³ | DC Resistance (mΩ) Max | Package Size (mm) |
|-------------------|--------------------------------|------------------------------------|------------------------|-----------------------|
| PA4306.102NLT | 1.0 | 5.9 | 33 | 7.3 x 7.3 x 3.1mm Max |
| PA4306.152NLT | 1.5 | 5.7 | 35 | |
| PA4306.222NLT | 2.2 | 5 | 45 | |
| PA4306.332NLT | 3.3 | 4 | 60 | |
| PA4306.472NLT | 4.7 | 3.3 | 72 | |
| PA4306.562NLT | 5.6 | 3 | 85 | |
| PA4306.682NLT | 6.8 | 2.7 | 120 | |
| PA4306.822NLT | 8.2 | 2.4 | 130 | |
| PA4306.103NLT | 10 | 2.1 | 140 | |
| PA4306.153NLT | 15 | 1.8 | 208 | |
| PA4306.223NLT | 22 | 1.5 | 286 | |
| PA4306.333NLT | 33 | 1.2 | 470 | |
| PA4306.473NLT | 47 | 1 | 640 | |
| PA4306.563NLT | 56 | 0.95 | 810 | |
| PA4306.683NLT | 68 | 0.82 | 975 | |
| PA4306.823NLT | 82 | 0.8 | 1053 | |
| PA4306.104NLT | 100 | 0.75 | 1210 | |
| PA4306.124NLT | 120 | 0.63 | 1690 | |
| PA4306.154NLT | 150 | 0.6 | 1820 | |
| PA4306.184NLT | 180 | 0.52 | 2340 | |
| PA4306.224NLT | 220 | 0.44 | 2700 | |
| PA4306.274NLT | 270 | 0.42 | 4030 | |
| PA4306.334NLT | 330 | 0.4 | 4680 | |
| PA4306.394NLT | 390 | 0.36 | 5070 | |
| PA4306.474NLT | 470 | 0.35 | 5720 | |
| PA4306.564NLT | 560 | 0.3 | 6630 | |
| PA4306.684NLT | 680 | 0.28 | 8580 | |
| PA4306.824NLT | 820 | 0.25 | 11800 | |
| PA4306.105NLT | 1000 | 0.22 | 14950 | |

Unshielded Drum Core Inductor

PA4306.XXXNL, PA4307.XXXNL & PA4308.XXXNL Series



| Electrical Specifications @ 25°C – Operating Temperature -40°C to 125°C | | | | |
|---|-------------------------------|------------------------------------|------------------------|-----------------------|
| Pulse Part Number | Inductance (uH) ¹² | Rated Current (A) Max ³ | DC Resistance (mΩ) Max | Package Size (mm) |
| PA4307.102NLT | 1.0 | 7.5 | 30 | 7.3 x 7.3 x 3.5mm Max |
| PA4307.152NLT | 1.5 | 7.3 | 38 | |
| PA4307.222NLT | 2.2 | 6.8 | 42 | |
| PA4307.332NLT | 3.3 | 5.4 | 60 | |
| PA4307.472NLT | 4.7 | 4.6 | 70 | |
| PA4307.562NLT | 5.6 | 4 | 85 | |
| PA4307.682NLT | 6.8 | 3.8 | 95 | |
| PA4307.822NLT | 8.2 | 3.4 | 130 | |
| PA4307.103NLT | 10 | 2.8 | 140 | |
| PA4307.153NLT | 15 | 2.5 | 285 | |
| PA4307.223NLT | 22 | 2 | 345 | |
| PA4307.333NLT | 33 | 1.8 | 425 | |
| PA4307.473NLT | 47 | 1.5 | 587 | |
| PA4307.563NLT | 56 | 1.3 | 610 | |
| PA4307.683NLT | 68 | 1.2 | 850 | |
| PA4307.823NLT | 82 | 1.1 | 1066 | |
| PA4307.104NLT | 100 | 1 | 1243 | |
| PA4307.124NLT | 120 | 0.9 | 1620 | |
| PA4307.154NLT | 150 | 0.8 | 1755 | |
| PA4307.184NLT | 180 | 0.75 | 2025 | |
| PA4307.224NLT | 220 | 0.63 | 2700 | |
| PA4307.274NLT | 270 | 0.6 | 2835 | |
| PA4307.334NLT | 330 | 0.55 | 3780 | |
| PA4307.394NLT | 390 | 0.5 | 4825 | |
| PA4307.474NLT | 470 | 0.44 | 5400 | |
| PA4307.564NLT | 560 | 0.4 | 7290 | |
| PA4307.684NLT | 680 | 0.35 | 9585 | |
| PA4307.824NLT | 820 | 0.32 | 10820 | |
| PA4307.105NLT | 1000 | 0.3 | 12295 | |

Unshielded Drum Core Inductor

PA4306.XXXNL, PA4307.XXXNL & PA4308.XXXNL Series



Electrical Specifications @ 25°C – Operating Temperature –40°C to 125°C

| Pulse Part Number | Inductance (uH) ^{1,2} | Rated Current (A) Max ³ | DC Resistance (mΩ) Max | Package Size (mm) |
|-------------------|--------------------------------|------------------------------------|------------------------|-----------------------|
| PA4308.102NLT | 1.0 | 12 | 35 | 7.3 x 7.3 x 4.8mm Max |
| PA4308.152NLT | 1.5 | 11 | 38 | |
| PA4308.222NLT | 2.2 | 9 | 42 | |
| PA4308.332NLT | 3.3 | 7.5 | 50 | |
| PA4308.472NLT | 4.7 | 6 | 65 | |
| PA4308.562NLT | 5.6 | 5.5 | 70 | |
| PA4308.682NLT | 6.8 | 5.2 | 84 | |
| PA4308.822NLT | 8.2 | 4.8 | 97 | |
| PA4308.103NLT | 10 | 4.3 | 125 | |
| PA4308.153NLT | 15 | 3.4 | 158 | |
| PA4308.223NLT | 22 | 2.9 | 225 | |
| PA4308.333NLT | 33 | 2.3 | 358 | |
| PA4308.473NLT | 47 | 1.9 | 486 | |
| PA4308.563NLT | 56 | 1.75 | 545 | |
| PA4308.683NLT | 68 | 1.6 | 660 | |
| PA4308.823NLT | 82 | 1.4 | 885 | |
| PA4308.104NLT | 100 | 1.3 | 1120 | |
| PA4308.124NLT | 120 | 1.23 | 1485 | |
| PA4308.154NLT | 150 | 1.1 | 1647 | |
| PA4308.184NLT | 180 | 1 | 1863 | |
| PA4308.224NLT | 220 | 0.92 | 2450 | |
| PA4308.274NLT | 270 | 0.8 | 2995 | |
| PA4308.334NLT | 330 | 0.7 | 3888 | |
| PA4308.394NLT | 390 | 0.65 | 4250 | |
| PA4308.474NLT | 470 | 0.57 | 5610 | |
| PA4308.564NLT | 560 | 0.53 | 7830 | |
| PA4308.684NLT | 680 | 0.48 | 10760 | |
| PA4308.824NLT | 820 | 0.42 | 12217 | |
| PA4308.105NLT | 1000 | 0.36 | 17550 | |

NOTES:

- Inductance tolerance is +/-30% for inductance values between 1uH and 8.2uH and +/-20% for values between 10uH and 680uH.
- Inductance is measured at 100kHz, 250mV
- The rated current as listed is the rms or heating current that the part can withstand with acceptable temperature rise in typical applications. At the listed current the inductance typically drops to 85%-90% of the no load value when measured at 25°C. The inductance is guaranteed to be greater than 65% of the no load inductance value when measured at 25°C.
- The temperature of the component (ambient plus temperature rise) must be within the stated operating temperature.
- Parts come in tape and reel packaging. Pulse complies with industry standard tape and reel specification EIA481. The tape and reel for this product has a width (W=16mm) and pitch (P=12mm).


Unshielded Drum Core Inductor

PA4306.XXXNL, PA4307.XXXNL & PA4308.XXXNL Series



Mechanical

PA43XX.XXXNL



PA4306.XXXNL - C Dimension is 3.1mm Max
 PA4307.XXXNL - C Dimension is 3.5mm Max
 PA4308.XXXNL - C Dimension is 4.8mm Max

Weight0.266 grams (PA4306)
0.314 grams (PA4307)
0.44 grams (PA4308)
Tape & Reel1000/reel

For More Information

Pulse Worldwide Headquarters

15255 Innovation Drive Ste 100
 San Diego, CA 92128
 U.S.A.

Pulse Europe

Pulse Electronics GmbH
 Am Rottland 12
 58540 Meinerzhagen
 Germany

Pulse China Headquarters

Pulse Electronics (ShenZhen) CO., LTD
 D708, Shenzhen Academy of
 Aerospace Technology,
 The 10th Keji South Road,
 Nanshan District, Shenzhen,
 P.R. China 518057

Pulse North China

Room 2704/2705
 Super Ocean Finance Ctr.
 2067 Yan An Road West
 Shanghai 200336
 China

Pulse South Asia

3 Fraser Street 0428
 DUO Tower
 Singapore 189352

Pulse North Asia

1F., No.111 Xiyuan Road
 Zhongli District
 Taoyuan City 32057
 Taiwan (R.O.C)

Tel: 858 674 8100
 Fax: 858 674 8262

Tel: 49 2354 777 100
 Fax: 49 2354 777 168

Tel: 86 755 33966678
 Fax: 86 755 33966700

Tel: 86 21 62787060
 Fax: 86 2162786973

Tel: 65 6287 8998
 Fax: 65 6280 0080

Tel: 886 3 4356768
 Fax: 886 3 4356820

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2019. Pulse Electronics, Inc. All rights reserved.