

PVA Short Stroke Key Switches



A
Pushbutton

Features/Benefits

- Compact design
- Short stroke to latch
- Wide variety of actuator heights
- Adapted for medium power applications
- RoHS compliant and compatible

Typical Applications

- Automotive (air conditioning, lighting)
- Industrial
- Control panel



Construction

FUNCTION: Momentary, Push-Push
 CONTACT ARRANGEMENT:
 PVA1: 2 make contacts (DPST)
 PVA2: 2 change over contacts (DPDT)
 SWITCHING MODE: Non-shorting
 TERMINALS: PC pins¹

Mechanical

TOTAL TRAVEL / LATCHING TRAVEL:
 OA: 2,4 mm
 EE: 2,4 / 1,5 mm
 ELECTRICAL TRAVEL: 0.8 mm (1.1 for PVA2 OA H5)
 OPERATING FORCE: 1,2N; 1,7N; 3,5N

Process

SOLDERABILITY:
 Wave soldering, compatible with lead free soldering profile
 Hand soldering, 350°C for 3 seconds

Note: Specifications listed above are for switches with standard options.
 For information on specific and custom switches, please contact technical support using the "Ask a Specialist" option on the PVA product web page.v

Electrical

SWITCHING POWER MAX.: 3 W DC
 SWITCHING VOLTAGE MAX.: 32 V DC
 SWITCHING CURRENT MAX.: 100 mA DC*
 DIELECTRIC STRENGTH (50 Hz / 1 min):
 1000 V between open contacts, PVA2: 750 V
 OPERATING LIFE:
 OA (momentary): $\geq 1 \times 10^5$ operations
 EE (push-push): $\geq 1 \times 10^6$ operations
 CONTACT RESISTANCE: Initial $\leq 100 \text{ m}\Omega$
 INSULATION RESISTANCE: $\geq 10^{10} \Omega$
 BOUNCE TIME: $\leq 3 \text{ ms}$

Environmental

OPERATING TEMPERATURE: -40°C to 85°C.²

- 1) "Snap-in" contacts on request, Version SNA with pins bent inside (standard)
- 2) With button +70°C

How To Order

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box. **Some of the configurations may not be available or could require some development.**

Switch



Button

Buttons must be ordered separately.
 Shipped in bulk.



*Compatible with H1 and H3 actuator models only.



PVA Short Stroke Key Switches

A

SERIES



Pushbutton

PVA1 (DPST)



PVA2 (DPDT)



MECHANICAL FUNCTION



OPTION CODE	FUNCTION
OA	Momentary
EE	Push-Push

OA



EE



11 Jun 18

Dimensions are shown: mm
Specifications and dimensions subject to change

PVA Short Stroke Key Switches




A

Pushbutton


TOTAL HEIGHT




H1 17,5 MM




H2 23 MM




H3 20,5 MM



H4 15 MM



H5 13 MM
(MOMENTARY ONLY)



OPERATING FORCE




- 1.2N** PVA1 ONLY
- 1.7N** PVA2 ONLY
- 3.5N**


TERMINATION



SNA with PVA1



SNA with PVA2




BUTTONS




BUTTONS MUST BE ORDERED SEPARATELY. SHIPPED IN BULK.

PE



PV



OPTION CODE	COLOR
RD	Red
GY	Gray
BK	Black
WH	White

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

C&K Switches:

[PVA2EEH2](#) [PVA2EEH1](#) [PVA1EEH1](#) [PVA2OAH2](#) [PVA2OAH1](#) [PVA1OAH2](#) [PVA1 OA H3](#) [PVA1 OA H4](#) [PVA1 EE H3](#) [PVA1 EE H4](#) [PVA2 OA H4](#) [PVA2 EE H3](#) [PVA2 EE H4](#) [PVA2 OA H3 1.7N](#) [PVA1EEH2](#) [PVA1EEH1SNA](#) [PVA1EEH1SNA3.5N](#) [PVA1EEH43.5N](#) [PVA1OAH1](#) [PVA2EEH1SNA](#) [PVA2EEH13.5N](#) [PVA1 EE H2 3.5N V2](#) [PVA1 EE H2 SNA V2](#) [PVA1 EE H3 3.5N V2](#) [PVA1 EE H3 3.5N SNA V2](#) [PVA1 EE H4 3.5N V2](#) [PVA1 EE H4 3.5N SNA V2](#) [PVA1 OA H1 3.5N V2](#) [PVA1 OA H2 SNA V2](#) [PVA1EEH13.5NV2](#) [PVA1 OA H1 2.2N V2](#) [PVA1 OA H3 3.5N V2](#) [PVA1 OA H4 3.5N V2](#) [PVA1 EE H1 2.2N V2](#) [PVA2OAH11.7NV2](#) [PVA1 EE H1 3.5N SNA V2](#) [PVA1 OA H1 V2](#) [PVA1 EE H1 V2](#) [PVA1 OA H2 V2](#) [PVA1 OA H1 3.5N SNA V2](#) [PVA1 OA H3 V2](#) [PVA1 OA H4 V2](#) [PVA1 EE H4 V2](#) [PVA1OAH11.2NV2](#) [PVA1OAH21.2NV2](#) [285-0205-000](#) [PVA2EEH11.7NV2](#) [PVA2EEH13.5NV2](#) [PVA2OAH53.5NV2](#) [PVA2OAH11.7NV2](#) [PVA10AH41.2NV2](#) [PVA10AH11.2NV2](#) [PVA2OAH41.7NV2](#) [PVA10AH21.2NV2](#) [PVA10AH4](#) [PVA2OAH5](#) [PVA10AH3](#) [PVA2OAH1](#) [PVA10AH4SNA](#) [PVA2OAH2](#) [PVA1EEH12.2N](#) [PVA2OAH12.2N](#) [PVA2EEH12.2N](#) [PVA1EEH33.5N](#) [PVA2OAH5SNA](#) [PVA2EEH4SNA3.5N](#) [PVA2EEH23.5N](#) [PVA2OAH1SNA3.5N](#) [PVA10AH12.2N](#) [PVA2OAH43.5N](#) [PVA2OAH3](#) [PVA2EEH4SNA](#) [PVA2EEH21.7NSNA](#) [PVA1EEH2SNA](#) [PVA2OAH33.5N](#) [PVA10AH33.5N](#) [PVA1EEH3SNA3.5N](#) [PVA2OAH4SNA](#) [PVA2EEH3SNA](#) [PVA2EEH33.5N](#) [PVA10AH2SNA](#) [PVA10AH13.5N](#) [PVA2OAH11.7NSNA](#) [PVA2OAH53.5N](#) [PVA2EEH1SNA3.5N](#) [PVA2OAH13.5N](#) [PVA10AH3SNA](#) [PVA1 OA H4 1.2N V2](#) [PVYE](#) [PVBU](#) [PEGN](#) [PVA2EEH21.7NSNAV2](#) [PVA1EEH11.2NV2](#) [PVA2EEH12.2NV2](#) [PVA2EEH33.5NV2](#) [PVA2EEH43.5NSNAV2](#) [PVA2EEH31.7NSNAV2](#) [PVA2EEH23.5NV2](#) [PVA1EEH11.2NSNAV2](#) [PVA2EEH21.7NV2](#)