

**Micro Commercial Components** 

Moisture Sensitivity Level 1

Small Surface Mount Type

DC Reverse Voltage

Mean Rectifying Current

Junction Temperature

Storage Temperature

Epoxy meets UL 94 V-0 flammability rating

Low Reverse Current and Low Forward Voltage.

Lead Free Finish/RoHS Compliant ("P" Suffix

gs

Rating

Peak Forward Surge Current(60Hz,1cyc)

designates RoHS Compliant. See ordering information)

**Features** 

**High Reliability** 

Marking : B

**Maximum Rat** 

Symbol

VR

 $I_0$ 

T<sub>STG</sub>

I<sub>FSM</sub>



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Rating

30

200

1

125

-40 to +125

Unit

V

mΑ


А

°C

°C

## **RB520S-30**

### 200 mA Schottky Barrier Diode 30 Volts



DIMENSIONS

MIN

1.50

1.10

0.01

0.25

0.08

0.50

0.51

ММ

MAX

1.70

1.30

0.85

0.07

0.35

0.15

0.70

0.77

INCHES

MAX

.067

.051 .033

.003

.014

.006

.028

.031

MIN

.059

.043

.030

.001

.010

.003

.020

.020

DIM

Α

B

D

G

### Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol Parameter Min Typ Max Units
------------------------------------


_					
	$V_{F}$	Forward Voltage (I <sub>F</sub> =200mAdc)	 	0.6	Vdc
	I <sub>R</sub>	Reverse Current (V <sub>R</sub> =10Vdc)	 	1.0	uAdc

www.mccsemi.com

NOTE

## RB520S-30





#### FIG. 3 - TYPICAL JUNCTION CAPACITANCE





FIG. 2 - REVERSE CHARACTERISTICS



#### FIG. 4 - TYPICAL FORWARD CURRENT DERATING CURVE 120 AVERAGE FORWARD CURRENT, (%) 100 80 60 40 20 0 150 ō 25 50 75 100 125 AMBIENT TEMPERATURE, (°C)

## www.mccsemi.com



### **Ordering Information :**

Device	Packing
Part Number-TP	Tape&Reel: 8Kpcs/Reel

### **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# www.mccsemi.com