


► General data



Header, nominal current: 12 A, rated voltage: 250 V, pitch: 5.08 mm, no. of positions: 15, mounting: Soldering

Order number	1759143
Type	MSTB 2,5/15-G-5,08

Barcode number	4017918030612
Unit pack	50 Pcs.
Customs tariff	85369010000

► Technical data

Dimensions / positions

Pitch	5.08 mm
Dimension a	71.12 mm
Number of positions	15
Pin dimensions	1 x 1 mm
Hole diameter	1.4 mm

Technical data

Insulating material group	IIIa
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV
Rated voltage (III/2)	320 V
Rated voltage (II/2)	400 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	12 A
Nominal voltage U_N	250 V
Maximum load current	12 A
Insulating material	PBT
Inflammability class acc. to UL 94	V0

► Certificates

UL


Nominal voltage U_N	300 V
Nominal current I_N	10 A

CSA


Nominal voltage U_N	300 V
Nominal current I_N	10 A

▶ Drawings

Drilling diagram



Dimensioned drawing



Approval logo



► Accessories

Item	Designation	Description
Assembly		
1759981	MSTB-BF	Mounting flange, for fixing both ends of the header onto the PCB, green insulating material, with M 2 x 14 screws and nuts.
1755477	MSTB-BL	Keying cap, for forming sections, plugs onto header pin, green insulating material
<hr/>		
Marking		
0804293	SK 5,08/3,8:FORTL.ZAHLEN	Marker card, printed horizontally, self-adhesive, 12 identical decades marked 1-10, 11-20 etc. up to 91-(99)100, sufficient for 120 terminal blocks
<hr/>		
Plug/Adapter		
1734401	CR-MSTB	Coding element, is inserted into the recess in the plug connection, red insulating material
<hr/>		

► Additional products

General

1873184	FKC 2,5/15-ST-5,08
1902246	FKCT 2,5/15-ST-5,08
1874086	FKCVR 2,5/15-ST-5,08
1873786	FKCVW 2,5/15-ST-5,08
1777413	FRONT-MSTB 2,5/15-ST-5,08
1786530	IC 2,5/15-G-5,08
1786077	ICV 2,5/15-G-5,08
1757145	MSTB 2,5/15-ST-5,08
1764251	MSTB 2,5/15-STZ-5,08
1808942	MSTBC 2,5/15-ST-5,08
1809637	MSTBC 2,5/15-STZ-5,08
1769146	MSTBP 2,5/15-ST-5,08
1781111	MSTBT 2,5/15-ST-5,08
1824489	MSTBU 2,5/15-ST-5,08-FL
1824256	MSTBU 2,5/15-STD-5,08
1831443	MSTBVK 2,5/15-ST-5,08
1792375	MVSTBR 2,5/15-ST-5,08
1792883	MVSTBW 2,5/15-ST-5,08
1918049	QC 0,75/15-ST-5,08
1883831	QC 1/15-ST-5,08
1826416	SMSTB 2,5/15-ST-5,08
1833946	UMSTBVK 2,5/15-ST-5,08

► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved