

MSTBO 2,5/ 4-G1L

Order No.: 1861060

Illustration shows different articles for putting together the upper part of the housing

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1861060>

Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Assembly: Soldering, Article with lateral pin exit

Commercial data	
GTIN (EAN)	 4 017918 155636
sales group	F057
Pack	50 pcs.
Customs tariff	85366990
Catalog page information	Page 294 (CC-2011)

Product notesWEEE/RoHS-compliant since:
01/01/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

CB, CSA, CUL, GOST, UL, VDE-PZI

Accessories

Item	Designation	Description
------	-------------	-------------

Assembly



1759981	MSTB-BF	Mounting flange, for fixing both ends of the header onto the PCB, green insulating material, with M 2 x 14 screws and nuts.
1755477	MSTB-BL	Keying cap, for forming sections, plugs onto header pin, green insulating material

General

2199618	CR MSTBO-G1	Coding section
---------	-------------	----------------

Diagrams/Drawings

Schematic diagram



Pin assignment left

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;