

MSTBO 2,5/ 4-G1R

Order No.: 1861073



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1861073>

Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn, Assembly: Soldering, Article with lateral pin exit

Commercial data	
GTIN (EAN)	4017918155650
sales group	F057
Pack	50 pcs.
Customs tariff	85366990
Weight/Piece	0.002809 KG
Catalog page information	Page 257 (CC-2009)

Product notes

WEEE/RoHS-compliant since:
01/01/2003



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

CB, CSA, CUL, GOST, UL, VDE-PZI

CSA

Nominal voltage U_N	300 V
Nominal current I_N	10 A

CUL

Nominal voltage U_N	300 V
Nominal current I_N	10 A

UL

Nominal voltage U_N	300 V
Nominal current I_N	10 A

Accessories



Item	Designation	Description
Assembly		
1759981	MSTB-BF	Mounting flange, for fixing both ends of the header onto the PCB, green insulating material, with M 2 x 14 screws and nuts.
1755477	MSTB-BL	Keying cap, for forming sections, plugs onto header pin, green insulating material

General

2199618	CR MSTBO-G1	Coding section
---------	-------------	----------------

Diagrams/Drawings

Schematic diagram



Pin assignment right

MSTBO 2,5/ 4-G1R Order No.: 1861073

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1861073>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;