

Varistors(SMD)


Conformity to RoHS Directive

Countermeasure for Surge and Static Electricity


AVR Series AVR-M, AVRL Types

Varistor (Variable resistor) is a nonlinear resistive element of the voltage dependence that resistance changes with applied voltage. Varistor is equivalent with Zener diode of two series connection. Therefore, do not have polarity.

CURRENT vs. VOLTAGE CHARACTERISTICS




EQUIVALENT CIRCUIT




THE EFFECT OF THE VARISTOR WITHOUT VARISTOR

A malfunction and failure of electronic equipment



WITH VARISTOR

Suppress abnormal voltage by inserting varistor in a circuit



FEATURES

- No polarity, due to symmetrical current-voltage characteristics. Equivalent to anode common type Zener diode.
- Excellent electrostatic absorption capability. Response is as good or better than Zener diode. Keeps symmetrical current-voltage characteristics even after electrostatic absorption.
- Adopted the inner electrodes lamination structure. Wide range of varistor voltages are available in series (8 to 39V). Low capacitance items are available in series (3.3pF to). World's smallest 0603-type, 1005-, 1608-, 2012-chip types and 1410-array type are available in series.
- Excellent mount reliability. Good for Pb-free soldering. Adopted (Ni/Sn) electroplating. Achieved good solderability and solder heat resistance.
- Can replace a Zener diode + capacitor combination. Reduced footprint and total mounting cost.

APPLICATIONS


- Electrostatic absorption
- Pulse noise absorption

TEMPERATURE RANGES


Type	AVR-M1005/1608/2012	AVR-M14A2/0603/AVRL
Operating	-40 to +125°C	-40 to +85°C
Storage	-40 to +125°C	-40 to +85°C

APPLICATION EXAMPLES

Consumer product	Application
Mobile phone	Data terminal
Digital video camera	LCD panel
Digital camera	Touch panel
PDA	Button and switch unit
Note PC	Battery terminal
DVD-ROM, CD-ROM	Audio-Video input-output terminal
CD/MD/MP3 player	Microphone/receiver unit
Game machine	Controller unit
In-car equipment	CAN-BUS
	ECU
	Connector
	Air conditioner panel
	Car audio
	Car navigation



INTERNAL STRUCTURE




CIRCUITS


SINGLE TYPE



ARRAY TYPE




OPERATIONAL VOLTAGE RANGES




RECOMMENDED REFLOW SOLDERING CONDITIONS

Sn-Pb SOLDERING



LEAD-FREE SOLDERING



AVR-M TYPE

PRODUCT IDENTIFICATION

AVR-M	1005	C	270	M	T	AAB
(1)	(2)	(3)	(4)	(5)	(6)	(7)

(1) Series name

(2) Dimensions L×W

0603	0.6×0.3mm
1005	1.0×0.5mm
1608	1.6×0.8mm
2012	2.0×1.2mm
14A2	1.4×1.0mm (2-element)

(3) Structure code

(4) Varistor voltage

270	27×10 ⁰ V
-----	----------------------

(5) Varistor voltage tolerance

K	±10%
M	±20%



(6) Packaging style

T	Taping
B	Bulk

(7) Capacitance and TDK internal code


SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN

0603/1005/1608/2012 TYPES



Dimensions in mm


Type	L	W	T	B min.	Weight (mg)typ.
0603	0.6±0.03	0.3±0.03	0.3±0.03	0.1	0.2
1005	1.0±0.05	0.5±0.05	0.5±0.05	0.1	1.2
1608	1.6±0.1	0.8±0.1	0.8±0.1	0.2	5
2012	2.0±0.2	1.25±0.2	1.0±0.2	0.2	15



Dimensions in mm


Type	a	b	c
0603	0.25 to 0.35	0.2 to 0.3	0.25 to 0.35
1005	0.3 to 0.5	0.35 to 0.45	0.4 to 0.6
1608	0.6 to 0.8	0.6 to 0.8	0.6 to 0.8
2012	0.9 to 1.2	0.7 to 0.9	0.9 to 1.2

1410 TYPE



Weight: 4mg typ.

Dimensions in mm



Dimensions in mm

ELECTRICAL CHARACTERISTICS


Part No.	Varistor voltage (Breakdown voltage) V _{1mA} (V)[DC1mA]		Maximum continuous voltage (Rated voltage) V _{dc} (V)	Clamping voltage V _{cl} (V) [8/20μs]	Maximum energy E(Joule) [10/1000μs]	Maximum peak current I _p (A) [8/20μs]	Capacitance C(pF) [1kHz, 1Vrms]	Packaging quantities (Taping) (pieces/reel)	
0603 type									
AVR-M0603C120M□*AAB	12	9.6 to 14.4	7.5 max.	23[1A]	0.01 max.	1 max.	33 typ.	15,000	
1005 type									
AVR-M1005C080M□AAB	8	6.4 to 9.6	5.5 max.	14[1A]	0.04 max.	25 max.	650 typ.	10,000	
AVR-M1005C080M□ADB	8	6.4 to 9.6	5.5 max.	14[1A]	0.01 max.	20 max.	480 typ.		
AVR-M1005C080M□ABB	8	6.4 to 9.6	5.5 max.	15[1A]	0.02 max.	3 max.	100 typ.		
AVR-M1005C080M□ACB	8	6.4 to 9.6	5.5 max.	19[1A]	0.01 max.	1 max.	33 typ.		
AVR-M1005C120M□AAB	12	9.6 to 14.4	7.5 max.	20[1A]	0.05 max.	10 max.	130 typ.		
AVR-M1005C270M□AAB	27	21.6 to 32.4	15 max.	50[1A]	0.06 max.	4 max.	40 typ.		
AVR-M1005C270M□ABB	27	21.6 to 32.4	15 max.	50[1A]	0.05 max.	1 max.	15 typ.	4,000	
1608 type									
AVR-M1608C080M□AAB	8	6.4 to 9.6	5.5 max.	15[2A]	0.09 max.	30 max.	650 typ.		
AVR-M1608C120M□6AB	12	9.6 to 14.4	7.5 max.	20[2A]	0.09 max.	50 max.	1050 typ.		
AVR-M1608C120M□2AB	12	9.6 to 14.4	7.5 max.	20[2A]	0.06 max.	15 max.	400 typ.		
AVR-M1608C180M□6AB	18	14.4 to 21.6	11 max.	30[2A]	0.1 max.	30 max.	600 typ.		
AVR-M1608C220K□6AB	22	19.8 to 24.2	16 max.	34[2A]	0.1 max.	30 max.	560 typ.		
AVR-M1608C220K□2AB	22	19.8 to 24.2	16 max.	37[2A]	0.03 max.	10 max.	210 typ.		
AVR-M1608C270K□6AB	27	24 to 30	19 max.	42[2A]	0.1 max.	48 max.	430 typ.		
AVR-M1608C270K□2AB	27	24 to 30	19 max.	42[2A]	0.1 max.	20 max.	160 typ.		
AVR-M1608C270K□ACB	27	24 to 30	19 max.	54[2A]	0.05 max.	10 max.	60 typ.		
AVR-M1608C270M□AAB	27	21.6 to 32.4	17 max.	52[2A]	0.05 max.	2 max.	30 typ.	2,000	
AVR-M1608C270M□ABB	27	21.6 to 32.4	17 max.	52[2A]	0.05 max.	2 max.	15 typ.		
2012 type									
AVR-M2012C120M□6AB	12	9.6 to 14.4	7.5 max.	20[5A]	0.2 max.	60 max.	1000 typ.	2,000	
AVR-M2012C220K□6AB	22	19.8 to 24.2	16 max.	38[5A]	0.3 max.	100 max.	800 typ.		
AVR-M2012C390K□6AB	39	35 to 43	28 max.	62[5A]	0.3 max.	100 max.	430 typ.		
1410 type									
AVR-M14A2C240M□600	24	20 to 27	16 max.	50[1A]	0.01 max.	5 max.	60 typ.[1MHz]	4,000	
AVR-M14A2C270M□470	27	21.6 to 32.4	15 max.	54[1A]	0.007 max.	5 max.	47 typ.[1MHz]		
AVRM14A2C270M□3R3F	27	21.6 to 32.4	10 max.	45[0.2A]	0.002 max.	0.2 max.	3.3 typ.[1MHz]		

* □ : Packaging style(T: Taping/B: Bulk)


TERMINOLOGY

Item	Unit	Terminology
Varistor voltage (Breakdown voltage)	V_{1mA} (V)	Voltage measured across the varistor when DC1mA is applied.
Maximum continuous voltage (Rated voltage)	V_{dc} (V)	Maximum DC voltage that can be applied continuously. Varistor leakage current: 50 μA max. (Within the range of maximum allowable circuit voltage)
Clamping voltage	V_{cl} (V)	Voltage appearing across the varistor when a pulse current (8/20 μs^*) of specified peak value is applied.
Maximum energy	E (Joule)	Maximum energy that can be absorbed without deteriorating varistor characteristics when an impulse (10/1000 μs^*) is applied once.
Maximum peak current	I_p (A)	Maximum current that can be withstood without deteriorating varistor characteristics when an impulse current (8/20 μs^*) is applied once.
Capacitance	C (pF)	Capacitance measured at 1kHz (or 1MHz) of oscillator frequency and 1Vrms of oscillator voltage.

*1 8/20 μs test waveform



*2 10/1000 μs test waveform



AVRL TYPE

PRODUCT IDENTIFICATION

AVRL	10	1A	3R3	F	T	A
(1)	(2)	(3)	(4)	(5)	(6)	(7)

(1) Series name

(2) Dimensions L×W

10	1.0×0.5mm
16	1.6×0.8mm

(3) Maximum continuous voltage

1A	10Vdc
----	-------

(4) Capacitance

1R1	1.1pF
3R3	3.3pF
6R8	6.8pF

(5) Capacitance tolerance


N	±0.3pF
F	±1pF
G	±2pF

(6) Packaging style

T	Taping
B	Bulk


(7) Varistor voltage and TDK internal code

SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN



Dimensions in mm

Type	L	W	T	B min.	Weight (mg)typ.
1005	1.0±0.05	0.5±0.05	0.5±0.05	0.1	1.2
1608	1.6±0.1	0.8±0.1	0.8±0.1	0.2	5



Dimensions in mm

Type	a	b	c
1005	0.3 to 0.5	0.35 to 0.45	0.4 to 0.6
1608	0.6 to 0.8	0.6 to 0.8	0.6 to 0.8

ELECTRICAL CHARACTERISTICS

Part No.	Capacitance C(pF) [1MHz, 1Vrms]	Maximum continuous voltage (Rated voltage) Vdc(V)	Insulation resistance Rdc(MΩ) [DC3V]	Varistor voltage V1mA(V)[DC1mA]	Packaging quantities (Taping) (pieces/reel)
1005 type					
AVRL101A1R1N□*A	1.1[0.8 to 1.4]	10 max.	10 min.	90 typ.	10,000
AVRL101A1R1N□B	1.1[0.8 to 1.4]	10 max.	10 min.	39 typ.	
AVRL101A3R3F□A	3.3[2.3 to 4.3]	10 max.	10 min.	27 typ.	
AVRL101A6R8G□A	6.8[4.8 to 8.8]	10 max.	10 min.	27 typ.	
1608 type					
AVRL161A1R1N□A	1.1[0.8 to 1.4]	10 max.	10 min.	90 typ.	4,000
AVRL161A1R1N□B	1.1[0.8 to 1.4]	10 max.	10 min.	39 typ.	
AVRL161A3R3F□A	3.3[2.3 to 4.3]	10 max.	10 min.	27 typ.	
AVRL161A6R8G□A	6.8[4.8 to 8.8]	10 max.	10 min.	27 typ.	


* □ : Packaging style(T: Taping/B: Bulk)

TERMINOLOGY


Item	Unit	Terminology
Capacitance	C (pF)	Capacitance measured at 1MHz of oscillator frequency and 1Vrms of oscillator voltage.
Maximum continuous voltage (Rated voltage)	Vdc (V)	Maximum DC voltage that can be applied continuously. Varistor leakage current: 50μA max. (Within the range of maximum allowable circuit voltage)
Insulation resistance	Rdc (MΩ)	Insulation resistance appearing across the varistor when specified voltage is applied.
Varistor voltage (Breakdown voltage)	V1mA (V)	Voltage measured across the varistor when DC1mA is applied.

TYPICAL ELECTRICAL CHARACTERISTICS


CURRENT vs. VOLTAGE CHARACTERISTICS




IMPEDANCE vs. FREQUENCY CHARACTERISTICS



TRANSMISSION CHARACTERISTICS



CAPACITANCE vs. FREQUENCY CHARACTERISTICS




ELECTROSTATIC DISCHARGE TESTS

TEST CONDITIONS


150pF, 330Ω contact discharge

Charged voltage /8kV, 0.1s interval


MEASURING CIRCUIT




AVR-M0603 TYPE




AVR-M1005 TYPE



AVR-M1608 TYPE




AVRL101A3R3F




ELECTROSTATIC ABSORPTION CHARACTERISTICS

DISCHARGE CURRENT WAVEFORM




DISCHARGE VOLTAGE WAVEFORM



WAVEFORM PARAMETERS [IEC61000-4-2]



Test level	ESD Charge voltage (kV)	First peak current of discharge (A)	Rise time (ns)
1	2	7.5	0.7 to 1.0
2	4	15	0.7 to 1.0
3	6	22.5	0.7 to 1.0
4	8	30	0.7 to 1.0

MEASURING CIRCUIT



ESD ABSORPTION CHARACTERISTICS

COMPARISON OF VARIOUS ELEMENTS



MERITS OF REPLACEMENT FROM ZENER DIODE


(1) Reduction in the number of parts

(2) Reduction in mounting cost

COMPARISON OF FOOTPRINT


Zener diode

Chip varistor



Save a mount area 65% down


EXAMPLE OF REPLACEMENT AT AUDIO TERMINAL



: Chip varistor

(3) Improved electrostatic absorption capability

COMPARE DATA OF CHIP VARISTOR AND ZENER DIODE ABOUT IC PROTECTION



CMOS: D74HC04C

ESD generator : Noise Laboratory Co.,Ltd., ESS -630A


200pF-0Ω method model equipment

Contact type discharge

ESD applied point: Vcc-ground

APPLICATION EXAMPLES

CELLULAR PHONE



AUDIO/VIDEO

