


Spec Sheet

MLCC (High dielectric type) for Industrial / Automotive Comfort and Safety Applications

GMK212BJ224KGHT



■ Features

- Item Summary
35V, X5R, 0.22 μ F, \pm 10%, 0805
- Lifecycle Stage
Mass Production
- AEC-Q200 qualified
- Standard packaging quantity (minimum)
Taping Embossed 3000pcs

■ Products characteristics table

CaseSize (EIA/JIS)	0805/2012
Rated Voltage (max)	35V
Capacitance	0.22 μ F
Capacitance Tolerance	\pm 10%
Resistance	500 M Ω μ F
Dielectric Loss Tangent	3.5%MAX
Temperature Characteristics (EIA/JIS)	X5R/-
Temperature Range (EIA/JIS)	-55 to +85 $^{\circ}$ C/-
Capacitance Change (EIA/JIS)	\pm 15/-%
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

■ External Dimensions

L	2.0mm \pm 0.10
W	1.25mm \pm 0.10
T	1.25mm \pm 0.10
e	0.5mm \pm 0.25

2013.08.20

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
Before making final selection, please check product specification.