



Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA91311
Phone:(818)-701-4933
Fax: (818)-701-4939

Features

- Internal Short Circuit Current Limiting
- Internal Thermal Overload Protection
- No External Components Required
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0

Maximum Ratings


Parameter	Symbol	Value	Unit
Input Voltage ($V_o=5.8V$)	V_1	30	V
Operating Junction Temperature	T_{OPR}	-20---+120	°C
Storage Temperature Range	T_{STG}	-55---+150	°C

Electrical Characteristics ($V_1=10V$, $I_o=40mA$, $0^\circ C < T_j < 125^\circ C$, $C_1=0.33\mu F$, $C_o=0.1\mu F$, unless otherwise specified)

Parameter	Sym	Min	Typ	Max	Test conditions
Output Voltage	V_o	4.8V	5.0V	5.2V	$T_j=25^\circ C$
		4.7V		5.25V	$7V \leq V_1 \leq 20V$, $I_o=1mA-40mA$
		5.0V		5.25V	$7V \leq V_1 \leq V_{MAX}$, $I_o=1mA-700mA$ (Note)
Load Regulation	ΔV_o		11mV	60mV	$I_o=1mA-100mA$, $T_j=25^\circ C$
			5.0mV	30mV	$I_o=1mA-40mA$, $T_j=25^\circ C$
Line regulation	ΔV_o		8mV	150mV	$7V \leq V_1 \leq 20V$, $T_j=25^\circ C$
			6mV	100mV	$8V \leq V_1 \leq 20V$, $T_j=25^\circ C$
Quiescent Current	I_q		2.0mA	5.5mA	$8V \leq V_1 \leq 20V$
Quiescent Current Change	ΔI_q			0.1mA	$1mA \leq I_o \leq 40mA$
Output Noise Voltage	V_N		40μV		$10Hz \leq f \leq 100KHz$
Ripple Rejection	RR	41dB	80dB		$8V \leq V_1 \leq 20V$, $f=120Hz$, $T_j=25^\circ C$
Dropout Voltage	V_d		1.7V		$T_j=25^\circ C$

*Note: Bypass Capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators



Typical Application:



MC78L05F

Three-Terminal Low Current Positive Voltage Regulator

SOT-89




1. OUT
2. GND (Case)
3. IN

DIM	INCHES		MM		NOTES
	MIN	MAX	MIN	MAX	
A	.173	.181	4.39	4.60	
B	.061	-----	1.55	-----	REF.
C	.154	.165	3.91	4.19	
D	.031	.039	0.80	1.00	
E	.092	.100	2.34	2.54	
F	.118	-----	3.00	-----	TYP
G	.013	.019	0.33	0.48	
H	.015	.021	0.38	0.53	
J	.015	.016	0.38	0.41	
K	.055	.063	1.40	1.60	

www.mccsemi.com

MC78L05F

Figure 1. Representative Schematic Diagram



*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes .
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****APPLICATIONS DISCLAIMER*****

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical,
Aerospace or Military Applications.