


## SMD Power Inductors (NR series)

## NR3015T470M



## ■ Features

- Item Summary  
47  $\mu$ H( $\pm$ 20%), 320mA, 300mA
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping 2000pcs

## ■ Products characteristics table

CaseSize (EIA/JIS)	-/3015
Inductance	47 $\mu$ H( $\pm$ 20%)
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	320mA
Rated Current -Temperature Rise Current	300mA
DC Resistance (max)	1.608 $\Omega$
Avg. of DC.Resistance	1.34 $\Omega$
Temperature Range	-25 $^{\circ}$ C to 120 $^{\circ}$ C
Self-resonant Frequency (min)	17MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

## ■ External Dimensions

L	3mm $\pm$ 0.1
W	3mm $\pm$ 0.1
H	1.5mm max

2013.02.24

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.