

Spec Sheet

MLCC (High dielectric type) for Industrial / Automotive Comfort and Safety Applications

UMK316B7474KLHT



■ Features

- Item Summary
50V, X7R, 0.47 μ F, \pm 10%, 1206
- Lifecycle Stage
Mass Production
- AEC-Q200 qualified
- Standard packaging quantity (minimum)
Taping Embossed 2000pcs

■ Products characteristics table

| | |
|---------------------------------------|----------------------------|
| CaseSize (EIA/JIS) | 1206/3216 |
| Rated Voltage (max) | 50V |
| Capacitance | 0.47 μ F |
| Capacitance Tolerance | \pm 10% |
| Resistance | 500 M Ω μ F |
| Dielectric Loss Tangent | 3.5%MAX |
| Temperature Characteristics (EIA/JIS) | X7R/- |
| Temperature Range (EIA/JIS) | -55 to +125 $^{\circ}$ C/- |
| Capacitance Change (EIA/JIS) | \pm 15/-% |
| RoHS Compliance | Yes |
| Halogen Free | Yes |
| Soldering Method | Reflow |

■ External Dimensions

| | |
|---|-------------------|
| L | 3.2mm \pm 0.15 |
| W | 1.6mm \pm 0.15 |
| T | 1.6mm \pm 0.20 |
| e | 0.5mm +0.35:-0.25 |

2013.08.20

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
Before making final selection, please check product specification.