




Close Window

<p><b>Inductors (Coils)</b></p> <p><b>Inductor Coils</b></p> <p>Part Number : <b>VLF5010ST-2R2M2R0</b></p> <p>Product Name : <b>Wire Wound Inductor for Power Line</b></p> <p>TDK Series Name : <b>VLF Series</b></p> <p>Application :</p> <p><b>DVCs, DSCs, PDAs, LCD displays, cellular phones, HDDs, etc.</b></p> <p>Function :</p> <p><b>Miniature size, Mount area: 4.6x4.8mm, Height: 1.0mm max. Generic use for portable DC to DC converter line. High magnetic shield construction should actualize high resolution for EMC protection. Available for automatic mounting in tape and reel package. The products do not contain lead and support lead-free soldering.</b></p> <p>Description :</p> <p><b>These are compact inductors for power line measuring at L4.6xW4.8mm and 1.0mm in height, considerably smaller compared to inductors with comparable characteristics.</b></p> <p><a href="#">Submit Sample Request</a></p> <p><a href="#">Check Distributor Inventory</a></p> <p><a href="#">Print Page</a></p> <p><a href="#">Download Adobe PDF Viewer</a></p>	<p><b>VLF5010S TYPE APPEARANCE PHOTOGRAPH</b></p> <div style="text-align: center;">  </div> <p style="text-align: center;">&lt; Prev   No PDF Available   Next &gt;</p>
<p><b>Additional Search Tools:</b></p> <p> <a href="#">Application</a>               <a href="#">Catalog</a>               <a href="#">SEAT</a>               <a href="#">CCV</a>               <a href="#">TVCL</a>               <a href="#">Tech Notes</a> </p>	

Property Name	Property Description
Product Lifecycle Stage	<b>Production</b>
Part Number Replacement	<i>No Data Available.</i>
Lead (Pb) Free	<b>Yes</b>
Surface Mount	<b>Yes</b>
Construction Type	<b>WIRE-WOUND</b>
Shape	<b>SMD</b>
Body Length (L)	Nom <b>4.8</b> mm
Body Breadth (W)	Nom <b>4.6</b> mm
Body Height (T)	Nom <b>1</b> mm
Inductance	Nom <b>2.2</b> $\mu$ H
Inductance Tolerance (%)	Min <b>-20</b> % Max <b>20</b> %
Frequency of Inductance	Nom <b>1</b> MHz
Q	Min <i>No Data Available.</i>
Frequency of Q	Nom <i>No Data Available.</i>
Self Resonant Frequency	Min <i>No Data Available.</i>
D.C. Resistance	Nom <b>0.064</b> Ohm
D.C. Resistance	Max <b>0.077</b> Ohm
Rated Current	Max <b>2</b> A
Terminal Material	<b>Copper alloy / Tin</b>
Polarity Marking	<b>No</b>
Magnetic Shielding	<b>Yes</b>
Soldering Method	<b>Reflow</b>
Measuring Equipment(L, Q, Rdc)	<b>L?F4285A , Rdc?FVP2941A or equivalent</b>
Category Temperature Range	Min <b>-40</b> Cel Max <b>105</b> Cel
Storage Temperature Range	Min <b>-40</b> Cel Max <b>105</b> Cel
Country of Origin	<b>JPN, CHN</b>
Packing	<b>Blister (Plastic)Taping [180mm Reel]</b>
Minimum Package Qty	Nom <b>1000</b> Pcs
Minimum Order Qty	Nom <b>1000</b> Pcs
Weight	Nom <b>0.07</b> g
<p>Disclaimer: This information is to be used for reference purposes only and is subject to change by TDK without notice. It reflects an overview of the product characteristics/performance for the particular part number. For product specification information, please refer to TDK's general product specification. Please note that this standard part is not designed or warranted to meet any specifications of any intermediate or end user different from or in addition to the specifications set fort in TDK's general product specification. Note also that this standard part has not been specially designed or manufactured for, nor is it intended or warranted for use in , or permitted to be resold for, specialized applications such as aviation, medical, and/or governmental/military applications (collectively, "Excluded Applications").</p>	



© TDK U.S.A. Corporation 2009. TDK Logo is a trademark or registered trademark of TDK Corporation.  
(Processing Time: 0.8778) Privacy Statement.