



WINSLOW ADAPTICs

Data Sheet – 0.64mm Square Post Unshrouded Header W811xxT38xxRC and W811xxG03xxRC series



Solutions to Component Leadtime and Obsolescence

Also available from Winslow Adaptics are cost effective, time saving solutions to test, obsolescence, supply problems and upgrades. OEMs can upgrade equipment with custom Adaptics utilising additional logic, often saving considerable cost and time on re-design. If lead-time becomes an issue contact us for a suitable package converter. We specialise in conversion of all package lead-frames. For further information please contact your nearest sales office

WINSLOW ADAPTICs

Data Sheet – 0.64mm Square Post Unshrouded Header W811xxT38xxRC and W811xxG03xxRC series

Replace 'xx' in part number with desired suffix from list below
36 is the maximum number of pins for the SIL version—replace to required size

SUFFIX	DIM A	DIM B
40	3.00	4.60
41	3.50	3.50
00	5.70	2.56
06	5.70	3.06
30	5.70	5.80
02	5.70	7.56
09	5.70	10.06
10	5.70	12.76
11	5.80	2.54
01	5.80	2.96
05	5.80	3.46
08	6.00	4.96
39	6.00	19.00
15	6.70	3.26
14	7.00	2.96
25	7.00	3.00
28	7.00	5.11
18	7.00	10.06
23	7.50	2.54
07	8.50	2.46
26	8.50	3.00
24	9.00	2.54
37	11.00	3.06
17	12.00	4.46
16	12.70	3.06
29	12.70	5.11
12	12.75	5.73
27	12.90	3.00
13	14.50	2.96

Can't see what you want? Call us with your enquiry: 0044 1874 625555

WINSLOW ADAPTICs

Data Sheet – 0.64mm Square Post Unshrouded Header W811xxT38xxRC and W811xxG03xxRC series

General Specifications

Unless stated all values are typical.

Contact

Resistance: 20 Milliohms Max
 Current Rating: 1 amp max.
 Dielectric Withstanding Voltage: AC 650 Volts RMS at Sea Level
 Material: Half Hard Brass.
 Plating: Tin: 6.0 microns pure bright tin over 2.5 microns nickel.
 Gold: Au/Ni 0.10µm Gold over 2.5µm Nickel

Moulding

Material: 30% Glass Fibre-Reinforced Polyester (Polybutylene Terephthalate - PBT)
 Insulation Resistance: 5000 MΩ(contact to contact) at 500VDC
 Arc Resistance: 145 seconds at 23 °C
 Electrical Strength: 121KV/cm at 23 °C
 Dielectric Constant: 3.9 (48 hrs 90%RH) at 100Hz 23 °C
 4.5 at 100Hz 121 °C
 3.7 (48 hrs 90%RH) at 1MHz 23 °C
 4.3 at 1MHz 121 °C
 Dissipation Factor: 0.0077 (48 hrs 30%RH) at 100Hz 23 °C
 0.0300 at 100Hz 121 °C
 0.0150 (48 hrs 30%RH) at 1MHz 23 °C
 0.0200 at 1MHz 121 °C
 Volume Resistivity: 3 x 10¹³Ω-CM (48 hrs 90%RH) at 25 °C
 10¹³ohms-CM at 121 °C
 Operating Temperature: -65 °C to 150 °C
 Flammability: UL94V-0


sales@winslowadaptics.com

DIP Support products from Winslow Adaptics


www.winslowadaptics.com





Custom Upgrades



Package



Conversion



Pitch Change

Also available from Winslow Adaptics are cost effective, time saving solutions to test, obsolescence, supply problems and upgrades. OEMs can upgrade equipment with custom Adaptics utilising additional logic, often saving considerable cost and time on re-design. If lead-time becomes an issue contact us for a suitable package convertor. We specialise in conversion of all package lead-frames.

sales@winslowadaptics.com

www.winslowadaptics.com